

The **flexisym** package

Authors: Michael J. Downes, Morten Høgholm
Maintained by Morten Høgholm, Will Robertson
Feedback: <https://github.com/wspr/breqn/issues>

2021/10/28 0.98l

User's guide

For now, the user's guide is in breqn.

Implementation

1 flexisym

```
1 {*package}
2 \RequirePackage{expl3}[2009/08/05]
3 \ProvidesExplPackage{flexisym}{2021/10/28}{0.98l}{Make math characters macros}
4
5 \edef\do{%
6   \noexpand\AtEndOfPackage{%
7     \catcode\number`'=\\number\catcode`\
8     \relax
9   }%
10 }
11 \do \let\do\relax
12 \catcode`'=12
13 \let@\sym@\gobble
14 \DeclareOption{robust}{%
15   \def@\sym#1{%
16     \ifx\protect\@typeset@protect \else\protect#1\exp_after:wN\use_none:n\fi
17   }%
18 }
```

The math groups (mg) here relate to \textfontn.

```
19 \def\mg@bin{2}{} binary operators
20 \def\mg@rel{2}{} relations
21 %%\def\mg@nre{B}{} negated relations
22 \def\mg@del{3}{} delimiters
```

```

23 %%\def\mg@arr{B}%
24 \def\mg@acc{0}%
25 \def\mg@cop{3}%
26 \def\mg@latin{1}%
27 \def\mg@greek{1}%
28 \def\mg@Greek{0}%
29 %%\def\mg@bflatin{4}%
30 \def\mg@Bbb{B}%
31 \def\mg@cal{2}%
32 %%\def\mg@frak{5}%
33 \def\mg@digit{0}%

```

This is how we insert mathchars. The command has three arguments: class, fam and slot position and so it is always given as hexadecimal. This way of separating things should make it easier to get this to work with XeTeX et al. which have many more slot positions

```

34 \cs_set_protected:Nn \math_char:NNn {
35   \tex_mathchar:D \__int_eval:w "#1#2#3 \__int_eval_end:
36 }

```

Delimiters and radicals are similar except here we have both small and large variant. Radicals have no class.

```

37 \cs_set_protected:Nn \math_delimiter:NNnNn {
38   \tex_delimiter:D \__int_eval:w "#1#2#3#4#5 \__int_eval_end:
39 }
40 \cs_set_protected:Nn \math_radical:NnNn {
41   \tex_radical:D \__int_eval:w "#1#2#3#4 \__int_eval_end:
42 }
43 \cs_set_protected:Nn \math_accent:NNnn {
44   \tex_mathaccent:D \__int_eval:w "#1 #2 #3 \__int_eval_end: {#4}
45 }
46
47 \let\sumlimits\displaylimits
48 \let\intlimits\nolimits
49 \let\namelimits\displaylimits

```

TEX defines eight types of atoms.

0. Ordinary
1. Operators
2. Binary
3. Relation
4. Open
5. Close
6. Punctuation
7. Inner

TeX defines eight math classes.

0. Ordinary
1. Operators
2. Binary
3. Relation
4. Open
5. Close
6. Punctuation
7. Variable family

flexisym/breqn extends this to types of classes.

0. Ordinary: (Ord), Bidirectional delimiters (DeB), Radicals (Rad), Accented items (Acc)
1. Operators: Cumulative Operators sum-like (COs), Cumulative Operators integral-like (COi)
2. Binary: (Bin)
3. Relation: (Rel), Arrow delimiters (DeA)
4. Open: (DeL)
5. Close (DeR)
6. Punctuation: (Pun)
7. Variable family: (Var)

Here's an overview of what we are about to do. Math chars of each type as defined by us need a basic operation for inserting it. We will call that function `\math_bsym_{<type>}:Nn`. Next there are compound symbols for each type which we name `\math_bcsym_{<type>}:Nn`. Also, there is inline mode and display mode which are different. We will call them for `\math_isym_{<type>}:Nn` `\math_icsym_{<type>}:Nn` for inline mode and `\math_dsym_{<type>}:Nn` and `\math_dcsym_{<type>}:Nn`. The code uses the terms `\math_sym_{<type>}:Nn` and `\math_csym_{<type>}:Nn` for the current meaning of things. First up the basic definitions. #1 is the math group it is from and #2 is the slot position.

```

50 \cs_new:Npn \math_bsym_Ord:Nn {\math_char:NNn 0 }% \m@Ord
51 \cs_new:Npn \math_bsym_Var:Nn {\math_char:NNn 7 }% \m@Var
52 \cs_new:Npn \math_bsym_Bin:Nn {\math_char:NNn 2 }% \m@Bin
53 \cs_new:Npn \math_bsym_Rel:Nn {\math_char:NNn 3 }% \m@Bin
54 \cs_new:Npn \math_bsym_Pun:Nn {\math_char:NNn 6 }% \m@Pun

```

```

55 \cs_new:Nn  \math_bsym_COs:Nn { \math_char:Nnn 1 #1 {#2} \sumlimits }% \m@COs
56 \cs_new:Nn  \math_bsym_COi:Nn { \math_char:Nnn 1 #1 {#2} \intlimits }% \m@COi
57 \cs_new:Nn  \math_bsym_DeL:Nn { \math_sd_del_aux:Nnn 4 #1{#2} }% \m@DeL
58 \cs_new:Nn  \math_bsym_DeR:Nn { \math_sd_del_aux:Nnn 5 #1{#2} }% \m@DeR
59 \cs_new:Nn  \math_bsym_DeB:Nn { \math_sd_del_aux:Nnn 0 #1{#2} }% \m@DeB
60 \cs_new:Nn  \math_bsym_DeA:Nn { \math_sd_del_aux:Nnn 3 #1{#2} }% \m@DeA
61 \cs_new:Nn  \math_bsym_Rad:Nn { \math_sd_rad_aux:Nn #1{#2} }% \m@Rad
62 \cs_new:Npn \math_bsym_Acc:Nn #1#2#3#4 {\mathAccent:Nnn #1#2{#3}{#4}}% name is wrong
63

```

Next is somewhat complicated internally. The way it is done is that delimiters and radicals need information about the smallest version of the symbol. If this smallest delimiter (SD) is defined, then use it. We have these functions to help us return the number. Extract the numbers to use and stick a function in front of it.

Code changed because now we require the smallest delimiter to be defined (it may be the same, no problem in that). So the two arguments present in `\math_bsym_DeL:Nn` are the location of extensible version (where the font will do the rest for us automatically). For each delimiter, a pointer is defined using the extensible characters family and slot as name and value equal to family and position of the smallest version. For (in standard L^AT_EX this is `{del}{00}` and `{OT1}{28}` respectively. Hence, `\math_bsym_DeL:Nn \mg@del {00}` must expand to `\math_delimiter>NNnNn 4 \mg@OT1 {28}\mg@del{00}`. So first expand away to get to the smallest version. Then call next function which shuffles the arguments around.

```

64 \cs_set:Npn \math_sd_del_aux:Nnn #1#2#3{
65   \exp_args:Nf \math_sd_del_auxi:nN {\use:c{sd@#2#3}} #1 #2{#3}
66 }
67 \cs_set:Npn \math_sd_del_auxi:nN #1#2{ \math_delimiter>NNnNn #2 #1 }

```

Same for radicals.

```

68 \cs_set:Npn \math_sd_rad_aux:Nn #1#2{
69   \exp_args:Nf \math_sd_rad_auxi:n {\use:c{sd@#1#2}} #1 {#2}
70 }
71 \cs_set:Npn \math_sd_rad_auxi:n #1{ \math_radical:NnNn #1 }
72
73
74 % \cs_set:Npn \math_sd_aux:nn #1#2 {
75 %   \%exp_args:Nnf \use:nn { #1} { \math_sd_auxi:Nn #2 }
76 %   \exp_args:Nnf \use:nn { #1} { \use:c{sd@\use:nn#2} }
77 % }
78 % \cs_set:Npn \math_sd_auxi:Nn #1#2 {
79 %   \cs_if_free:cTF {sd@#1#2}
80 %   { #1{#2} }
81 %   { \use:c{sd@#1#2} }
82 %

```

compound symbols here

```

83 \cs_set_protected:Npn \math_bcsym_Ord:Nn #1#2 { \csmode { \mathord { \OrdSymbol {#2} } }%
84 \cs_set_protected:Npn \math_bcsym_Var:Nn #1#2 { \csmode { \mathord { \OrdSymbol {#2} } } }%
85 \cs_set_protected:Npn \math_bcsym_Bin:Nn #1#2 { \csmode { \mathbin { \OrdSymbol {#2} } } }%

```

```

86 \cs_set_protected:Npn \math_bcsym_Rel:Nn #1#2 { \@symtype \mathrel { \OrdSymbol {#2} } }%
87 \cs_set_protected:Npn \math_bcsym_Pun:Nn #1#2 { \@symtype \mathpunct { \OrdSymbol {#2} } }%
88 \cs_set_protected:Npn \math_bcsym_Coi:Nn #1#2 { \@symtype \mathop { \OrdSymbol {#2} } \intl{#1} }%
89 \cs_set_protected:Npn \math_bcsym_COs:Nn #1#2 { \@symtype \mathop { \OrdSymbol {#2} } \sum_{#1}^{#2} }%
90 \cs_set_protected:Npn \math_bcsym_Del:Nn #1#2 { \@symtype \mathopen { \OrdSymbol {#2} } }%
91 \cs_set_protected:Npn \math_bcsym_DeR:Nn #1#2 { \@symtype \mathclose { \OrdSymbol {#2} } }%
92 \cs_set_protected:Npn \math_bcsym_DeB:Nn #1#2 { \@symtype \mathord { \OrdSymbol {#2} } }%
93 \cs_set_protected:Npn \math_bcsym_DeA:Nn #1#2 { \@symtype \mathrel { \OrdSymbol {#2} } }%
94 \cs_set_protected:Npn \math_bcsym_Acc:Nn { \@symtype \mathrel { \OrdSymbol {#2} } } }% \@symAcc FIX!
95 % These three?
96 \cs_set_protected:Npn \math_bcsym_Ope:Nn #1#2 { \@symtype \mathopen { \OrdSymbol {#2} } } }% \@symVar
97 \cs_set_protected:Npn \math_bcsym_Clo:Nn #1#2 { \@symtype \mathclose { \OrdSymbol {#2} } } }% \@symVar
98 \cs_set_protected:Npn \math_bcsym_Inn:Nn #1#2 { \@symtype \mathinner { \OrdSymbol {#2} } } }% \@symVar
99
100 \let\@symtype\@firstofone
101 \let\sym@\global\global

```

The inline variants, using the basic operations. Currently we do not do anything to inline math.

```

102 \cs_new:Npn \math_isym_Ord:Nn { \math_bsym_Ord:Nn } }% \m@Ord
103 \cs_new:Npn \math_isym_Var:Nn { \math_bsym_Var:Nn } }% \m@Var
104 \cs_new:Npn \math_isym_Bin:Nn { \math_bsym_Bin:Nn } }% \m@Bin
105 \cs_new:Npn \math_isym_Rel:Nn { \math_bsym_Rel:Nn } }% \m@Bin
106 \cs_new:Npn \math_isym_Pun:Nn { \math_bsym_Pun:Nn } }% \m@Pun
107 \cs_new:Npn \math_isym_COs:Nn { \math_bsym_COs:Nn } }% \m@COS
108 \cs_new:Npn \math_isym_Coi:Nn { \math_bsym_Coi:Nn } }% \m@COI
109 \cs_new:Npn \math_isym_DeL:Nn { \math_bsym_DeL:Nn } }% \m@DeL
110 \cs_new:Npn \math_isym_DeR:Nn { \math_bsym_DeR:Nn } }% \m@DeR
111 \cs_new:Npn \math_isym_DeB:Nn { \math_bsym_DeB:Nn } }% \m@DeB
112 \cs_new:Npn \math_isym_DeA:Nn { \math_bsym_DeA:Nn } }% \m@DeA
113 \cs_new:Npn \math_isym_Rad:Nn { \math_bsym_Rad:Nn } }% \m@Rad
114 \cs_new:Npn \math_isym_Acc:Nn { \math_bsym_DeL:Nn } }% name is wrong
115 % inline compound
116 \cs_set_protected:Npn \math_icsym_Ord:Nn { \math_bcsym_Ord:Nn }
117 \cs_set_protected:Npn \math_icsym_Var:Nn { \math_bcsym_Var:Nn }
118 \cs_set_protected:Npn \math_icsym_Bin:Nn { \math_bcsym_Bin:Nn }
119 \cs_set_protected:Npn \math_icsym_Rel:Nn { \math_bcsym_Rel:Nn }
120 \cs_set_protected:Npn \math_icsym_Pun:Nn { \math_bcsym_Pun:Nn }
121 \cs_set_protected:Npn \math_icsym_Coi:Nn { \math_bcsym_Coi:Nn }
122 \cs_set_protected:Npn \math_icsym_COs:Nn { \math_bcsym_COs:Nn }
123 \cs_set_protected:Npn \math_icsym_DeL:Nn { \math_bcsym_DeL:Nn }
124 \cs_set_protected:Npn \math_icsym_DeR:Nn { \math_bcsym_DeR:Nn }
125 \cs_set_protected:Npn \math_icsym_DeB:Nn { \math_bcsym_DeB:Nn }
126 \cs_set_protected:Npn \math_icsym_DeA:Nn { \math_bcsym_DeA:Nn }
127 \cs_set_protected:Npn \math_icsym_Acc:Nn { \math_bcsym_Acc:Nn }
128 \cs_set_protected:Npn \math_icsym_Ope:Nn { \math_bcsym_Ope:Nn }
129 \cs_set_protected:Npn \math_icsym_Clo:Nn { \math_bcsym_Clo:Nn }
130 \cs_set_protected:Npn \math_icsym_Inn:Nn { \math_bcsym_Inn:Nn }

```

The display variants, using the basic operations. Currently we do not do

anything to inline math.

```
131 \cs_new:Npn \math_dsym_Ord:Nn { \math_bsym_Ord:Nn }
132 \cs_new:Npn \math_dsym_Var:Nn { \math_bsym_Var:Nn }
133 \cs_new:Npn \math_dsym_Bin:Nn { \math_bsym_Bin:Nn }
134 \cs_new:Npn \math_dsym_Rel:Nn { \math_bsym_Rel:Nn }
135 \cs_new:Npn \math_dsym_Pun:Nn { \math_bsym_Pun:Nn }
136 \cs_new:Npn \math_dsym_COs:Nn { \math_bsym_COs:Nn }
137 \cs_new:Npn \math_dsym_COi:Nn { \math_bsym_COi:Nn }
138 \cs_new:Npn \math_dsym_DeL:Nn { \math_bsym_DeL:Nn }
139 \cs_new:Npn \math_dsym_DeR:Nn { \math_bsym_DeR:Nn }
140 \cs_new:Npn \math_dsym_DeB:Nn { \math_bsym_DeB:Nn }
141 \cs_new:Npn \math_dsym_DeA:Nn { \math_bsym_DeA:Nn }
142 \cs_new:Npn \math_dsym_Rad:Nn { \math_bsym_Rad:Nn }
143 \cs_new:Npn \math_dsym_Acc:Nn { \math_bsym_DeL:Nn }
144 % inline compound
145 \cs_set_protected:Npn \math_dcsym_Ord:Nn { \math_bcsym_Ord:Nn }
146 \cs_set_protected:Npn \math_dcsym_Var:Nn { \math_bcsym_Var:Nn }
147 \cs_set_protected:Npn \math_dcsym_Bin:Nn { \math_bcsym_Bin:Nn }
148 \cs_set_protected:Npn \math_dcsym_Rel:Nn { \math_bcsym_Rel:Nn }
149 \cs_set_protected:Npn \math_dcsym_Pun:Nn { \math_bcsym_Pun:Nn }
150 \cs_set_protected:Npn \math_dcsym_COi:Nn { \math_bcsym_COi:Nn }
151 \cs_set_protected:Npn \math_dcsym_COs:Nn { \math_bcsym_COs:Nn }
152 \cs_set_protected:Npn \math_dcsym_DeL:Nn { \math_bcsym_DeL:Nn }
153 \cs_set_protected:Npn \math_dcsym_DeR:Nn { \math_bcsym_DeR:Nn }
154 \cs_set_protected:Npn \math_dcsym_DeB:Nn { \math_bcsym_DeB:Nn }
155 \cs_set_protected:Npn \math_dcsym_DeA:Nn { \math_bcsym_DeA:Nn }
156 \cs_set_protected:Npn \math_dcsym_Acc:Nn { \math_bcsym_Acc:Nn }
157 \cs_set_protected:Npn \math_dcsym_Ope:Nn { \math_bcsym_Ope:Nn }
158 \cs_set_protected:Npn \math_dcsym_Clo:Nn { \math_bcsym_Clo:Nn }
159 \cs_set_protected:Npn \math_dcsym_Inn:Nn { \math_bcsym_Inn:Nn }
```

Almost ready now! Now just need two commands to initialize these settings.

```
160 \cs_set:Npn \math_setup_inline_symbols:
161 {
162   \cs_set_eq:NN \math_sym_Ord:Nn \math_isym_Ord:Nn
163   \cs_set_eq:NN \math_sym_Var:Nn \math_isym_Var:Nn
164   \cs_set_eq:NN \math_sym_Bin:Nn \math_isym_Bin:Nn
165   \cs_set_eq:NN \math_sym_Rel:Nn \math_isym_Rel:Nn
166   \cs_set_eq:NN \math_sym_Pun:Nn \math_isym_Pun:Nn
167   \cs_set_eq:NN \math_sym_COs:Nn \math_isym_COs:Nn
168   \cs_set_eq:NN \math_sym_COi:Nn \math_isym_COi:Nn
169   \cs_set_eq:NN \math_sym_DeL:Nn \math_isym_DeL:Nn
170   \cs_set_eq:NN \math_sym_DeR:Nn \math_isym_DeR:Nn
171   \cs_set_eq:NN \math_sym_DeB:Nn \math_isym_DeB:Nn
172   \cs_set_eq:NN \math_sym_DeA:Nn \math_isym_DeA:Nn
173   \cs_set_eq:NN \math_sym_Rad:Nn \math_isym_Rad:Nn
174   \cs_set_eq:NN \math_sym_Acc:Nn \math_isym_DeL:Nn
175   \cs_set_eq:NN \math_csym_Ord:Nn \math_icsym_Ord:Nn
176   \cs_set_eq:NN \math_csym_Var:Nn \math_icsym_Var:Nn
177   \cs_set_eq:NN \math_csym_Bin:Nn \math_icsym_Bin:Nn
```

```

178 \cs_set_eq:NN \math_csym_Rel:Nn \math_icsym_Rel:Nn
179 \cs_set_eq:NN \math_csym_Pun:Nn \math_icsym_Pun:Nn
180 \cs_set_eq:NN \math_csym_COi:Nn \math_icsym_COi:Nn
181 \cs_set_eq:NN \math_csym_COs:Nn \math_icsym_COs:Nn
182 \cs_set_eq:NN \math_csym_DeL:Nn \math_icsym_DeL:Nn
183 \cs_set_eq:NN \math_csym_DeR:Nn \math_icsym_DeR:Nn
184 \cs_set_eq:NN \math_csym_DeB:Nn \math_icsym_DeB:Nn
185 \cs_set_eq:NN \math_csym_DeA:Nn \math_icsym_DeA:Nn
186 \cs_set_eq:NN \math_csym_Acc:Nn \math_icsym_Acc:Nn
187 \cs_set_eq:NN \math_csym_Ope:Nn \math_icsym_Ope:Nn
188 \cs_set_eq:NN \math_csym_Clo:Nn \math_icsym_Clo:Nn
189 \cs_set_eq:NN \math_csym_Inn:Nn \math_icsym_Inn:Nn
190 }
191
192 \cs_set:Npn \math_setup_display_symbols:
193 {
194   \cs_set_eq:NN \math_sym_Ord:Nn \math_dsym_Ord:Nn
195   \cs_set_eq:NN \math_sym_Var:Nn \math_dsym_Var:Nn
196   \cs_set_eq:NN \math_sym_Bin:Nn \math_dsym_Bin:Nn
197   \cs_set_eq:NN \math_sym_Rel:Nn \math_dsym_Rel:Nn
198   \cs_set_eq:NN \math_sym_Pun:Nn \math_dsym_Pun:Nn
199   \cs_set_eq:NN \math_sym_COs:Nn \math_dsym_COs:Nn
200   \cs_set_eq:NN \math_sym_COi:Nn \math_dsym_COi:Nn
201   \cs_set_eq:NN \math_sym_DeL:Nn \math_dsym_DeL:Nn
202   \cs_set_eq:NN \math_sym_DeR:Nn \math_dsym_DeR:Nn
203   \cs_set_eq:NN \math_sym_DeB:Nn \math_dsym_DeB:Nn
204   \cs_set_eq:NN \math_sym_DeA:Nn \math_dsym_DeA:Nn
205   \cs_set_eq:NN \math_sym_Rad:Nn \math_dsym_Rad:Nn
206   \cs_set_eq:NN \math_sym_Acc:Nn \math_dsym_DeL:Nn
207   \cs_set_eq:NN \math_csym_Ord:Nn \math_dcsym_Ord:Nn
208   \cs_set_eq:NN \math_csym_Var:Nn \math_dcsym_Var:Nn
209   \cs_set_eq:NN \math_csym_Bin:Nn \math_dcsym_Bin:Nn
210   \cs_set_eq:NN \math_csym_Rel:Nn \math_dcsym_Rel:Nn
211   \cs_set_eq:NN \math_csym_Pun:Nn \math_dcsym_Pun:Nn
212   \cs_set_eq:NN \math_csym_COi:Nn \math_dcsym_COi:Nn
213   \cs_set_eq:NN \math_csym_COs:Nn \math_dcsym_COs:Nn
214   \cs_set_eq:NN \math_csym_DeL:Nn \math_dcsym_DeL:Nn
215   \cs_set_eq:NN \math_csym_DeR:Nn \math_dcsym_DeR:Nn
216   \cs_set_eq:NN \math_csym_DeB:Nn \math_dcsym_DeB:Nn
217   \cs_set_eq:NN \math_csym_DeA:Nn \math_dcsym_DeA:Nn
218   \cs_set_eq:NN \math_csym_Acc:Nn \math_dcsym_Acc:Nn
219   \cs_set_eq:NN \math_csym_Ope:Nn \math_dcsym_Ope:Nn
220   \cs_set_eq:NN \math_csym_Clo:Nn \math_dcsym_Clo:Nn
221   \cs_set_eq:NN \math_csym_Inn:Nn \math_dcsym_Inn:Nn
222 }

```

Phew, that was it.

Well, almost. We need to set them up for use properly. Should they be added to `\everymath?` Probably, for math within displays. However, this is a lot of extra processing which we could tackle in the display setup.

```

223 \math_setup_inline_symbols:
      Need an active character for a second. Don't rely on ~ being active!
224 \edef\tmp{\catcode\z@=\the\catcode\z@}
225 \catcode\z@=\active
226 \def\DeclareFlexSymbol#1#2#3#4{%
227   \begingroup
228   \cs_set_protected:Npx\@tempb{
229     \exp_not:N\@sym\exp_not:N#1\exp_not:c{math_sym_#2:Nn}%
230     \exp_not:c{mg@#3}{#4}%
231   }
232   \ifcat\exp_not:N#1\relax
233     \sym@global\let#1\@tempb
234   \else
235     \sym@global\mathcode`#1="8000\relax
236     \lccode\z@='#1\relax
237     \lowercase{\sym@global\let^{\@tempb}}% zero char
238   \fi
239   \endgroup
240 }
241 \tmp % restore catcode
242 \cs_set:Npn \DeclareFlexDelimiter #1#2#3#4#5#6{%
243   \DeclareFlexSymbol{#1}{#2}{#3}{#4}%
244   \cs_gset:cp{sd@\use:c{mg@#3}{#4}}{\exp_not:c{mg@#5}{#6}}%
245 }
246
\DeclareFlexCompoundSymbol{\cdots}{Inn}{\cdotp\cdotp\cdotp} \def\@symInn#1#2{\@syntyp
\@syntype \mathinner{\OrdSymbol{\cdotp\cdotp\cdotp}}}
247 \def\DeclareFlexCompoundSymbol#1#2#3{%
248   \exp_args:NNo \DeclareRobustCommand#1{\csname math_csym_#2:Nn\endcsname#1{#3}}%
249   \sym@global\let#1\relax
250 }
251 \DeclareRobustCommand{textchar}{\text@char{textfont}}
252 \DeclareRobustCommand{scriptchar}{\text@char{scriptfont}}%
Simplified the next bit because now the slot is read as one argument so no afterassignment and what have you. Just drop the char directly.
253 \def{text@char@sym#1#2#3#4}{% #3=fam, #4=slot
254   \begingroup
255     \cs_set_eq:NN \prg_do_nothing: % defense against infinite loops
the next line will result in \scriptfont<num>, where #3 provides the <num>.
256     \the{text@script@char#3}%
257     \char"#4\endgroup
258 }
259 \edef\tmp{\catcode\z@=\the\catcode\z@}
260 \catcode\z@=\active
261 \def{text@char#1#2}{\begingroup
262   \check@mathfonts
263   \cs_set_eq:NN \text@script@char #1

```

```

264 \cs_set_eq:NN \csmode \text@char@csmode
265 \cs_set_eq:NN \csmode@type \use_i:nn
266 \cs_set_eq:NN \OrdSymbol \use:n
267 \cs_set_eq:NN \ifmmode \iftrue
268 \everymath{\use:none:n}%
269 \def\mkern{\muskip{z@}}
270 \cs_set_eq:NN \mskip \mkern
271 \ifcat\relax\noexpand#2% true if #2 is a cs.
272   #2%
273 \else
274   \lccode{z@=\expandafter`\string#2\relax
275   \lowercase{`^`@}}%
276 \fi
277 \endgroup
278 }
279 \tmp % restore catcode
280 \providecommand\textprime{%
281 \DeclRobustCommand\textprime{\leavevmode
282   \raise.8ex\hbox{\text@char\scriptfont\prime}}%
283 }
284 \@ifundefined{resetMathstrut@}{}{%
285   \def\resetMathstrut@{%
286     \setbox{z@}\hbox{\textchar\vert}%
287     \ht{\Mathstrutbox@\ht{z@}\dp{\Mathstrutbox@\dp{z@}}%
288   }%
289 }
Arrow fills. changed to 7mu as in amsmath
290 \ifundefined{rightarrowfill@}{}{%
291   \def\rightarrowfill@{\m@th\setbox{h{\relbar}}\ht{z@}\z@%
292   \#1\copy{z@\mkern-7mu\cleaders
293   \hbox{\#1\mkern-2mu\box{z@\mkern-2mu}}\hfill
294   \mkern-6mu\OrdSymbol{\rightarrow}}$}
295 \def\leftarrowfill@{\m@th\setbox{h{\relbar}}\ht{z@}\z@%
296   \#1\OrdSymbol{\leftarrow}\mkern-6mu\cleaders
297   \hbox{\#1\mkern-2mu\copy{z@\mkern-2mu}}\hfill
298   \mkern-7mu\box{z@$}}
299 \def\leftrightarrowfill@{\m@th\setbox{h{\relbar}}\ht{z@}\z@%
300   \#1\OrdSymbol{\leftarrow}\mkern-6mu\cleaders
301   \hbox{\#1\mkern-2mu\box{z@\mkern-2mu}}\hfill
302   \mkern-6mu\OrdSymbol{\rightarrow}}$}
303 }
hey, this looks like a simple case switch...
304 \def\binrel@sym#1#2#3#4{%
305   \xdef\binrel@{\#1{%
306     \ifx\math_sym_Ord:Nn #2 \math_csym_Ord:Nn
307     \else\ifx\math_sym_Var:Nn#2 \math_csym_Var:Nn
308     \else\ifx\math_sym_COs:Nn#2 \math_csym_COs:Nn
309     \else\ifx\math_sym_COi:Nn#2 \math_csym_COi:Nn
310     \else\ifx\math_sym_Bin:Nn#2 \math_csym_Bin:Nn

```

```

311     \else\ifx\math_sym_Rel:Nn#2 \math_csym_Rel:Nn
312     \else\ifx\math_sym_Pun:Nn#2 \math_csym_Pun:Nn
313     \else\exp_not:N\@symErr \fi\fi\fi\fi\fi\fi
314     ?{\exp_not:N\OrdSymbol{##1}}}%
315 }
316
317 \def\binrel@a{%
318   \def\math_sym_Ord:Nn##1##2{\gdef\binrel@@####1{\math_sym_Ord:Nn##1{\OrdSymbol{####1}}}}%
319   \def\math_sym_Var:Nn##1##2{\gdef\binrel@@####1{\math_sym_Var:Nn##1{\OrdSymbol{####1}}}}%
320   \def\math_sym_COs:Nn##1##2{\gdef\binrel@@####1{\math_sym_COs:Nn##1{\OrdSymbol{####1}}}}%
321   \def\math_sym_COi:Nn##1##2{\gdef\binrel@@####1{\math_sym_COi:Nn##1{\OrdSymbol{####1}}}}%
322   \def\math_sym_Bin:Nn##1##2{\gdef\binrel@@####1{\math_sym_Bin:Nn##1{\OrdSymbol{####1}}}}%
323   \def\math_sym_Rel:Nn##1##2{\gdef\binrel@@####1{\math_sym_Rel:Nn##1{\OrdSymbol{####1}}}}%
324   \def\math_sym_Pun:Nn##1##2{\gdef\binrel@@####1{\math_sym_Pun:Nn##1{\OrdSymbol{####1}}}}}%
325 }
326 \def\binrel@#1{%
327   \setbox\z@\hbox{$%
328     \let\mathchoice@gobblethree
329     \let\@sym\binrel@sym \binrel@a
330     #1$}%
331 }
332 \def\@symextension{sym}
333 \newcommand\usesymbols[1]{%
334   \clist_map_variable:nNn{#1}\@tempb{%
335     \exp_args:No\c_onefilewithoptions{\@tempb}[] []\@symextension
336   }%
337 }
338 % Need to introduce \ProvidesExplFile somehow
339 \newcommand\ProvidesSymbols[1]{\ProvidesFile{#1.sym}}
340 \DeclareRobustCommand{\not}[1]{\math_csym_Rel:Nn\not{\OrdSymbol{\notRel#1}}}
341 \DeclareRobustCommand{\OrdSymbol}[1]{%
342   \begingroup\mathchars@reset#1\endgroup
343 }
344 \def\mathchars@reset{\let\@sym\@sym@ord \let\@symtype\@symtype@ord
345   \let\OrdSymbol\relax}
346 \def\@symtype@ord#1{}% a strange sort of \gobble
347 \def\@sym@ord#1#2{\exp_after:wN\@sym@ord@a\string#2@nil}%
348 \begingroup
349 \lccode`\.=`\_
350 \lowercase{\endgroup
351 \def\@sym@ord@a#1.#2.}{#3#4@nil#5#6}%
352 \if D#3
353   \%math_ord_delim_aux:Nn #5{#6}

```

```

353     \math_sd_del_aux:Nnn 0 #5{#6}%
354     \else
355     \math_char:NNn 0 #5{#6}
356     \fi
357 }
358 \cs_set:Nn \math_ord_delim_aux:Nn {
359   \math_sd_aux:nn { \math_char:NNn 0 } {#1{#2}}
360 }

```

Before declaring any math characters active, we have to take care of a small problem with `amsmath v2.x`, if it is loaded before `flexisym`. `\std@minus` and `\std@equal` are defined as

```

\mathchardef\std@minus\mathcode`-\relax
\mathchardef\std@equal\mathcode`=\relax

```

in `amsmath.sty` and again `\AtBeginDocument`. The latter is because

In case some alternative math fonts are loaded later. [`amsmath.dtx`]

The problem arises because `flexisym` sets the mathcode of all symbols to 32768 which is illegal for a `\mathchardef`.

We have to remove the assignments from the `\AtBeginDocument` hook as they will cause an error there.

```
361 \@ifpackageloaded{amsmath}{%
```

Split the contents of `\@begindocumenthook` by reading what we search for as a delimited argument and ensure these two assignments do not take place. It is questionable if anything reasonable can be done to them. In the case of a package such as `mathpazo` which defines

```
\DeclareMathSymbol{=}{\mathrel}{upright}{3D}
```

the `\Relbar` will look wrong if we don't use the correct symbol. The way to solve this is define additional `.sym` files which contain the definition of `\relbar` and `\Relbar` needed. We need those additional files anyway for things like `\joinord`.

```
362 }{}
```

There is problem when using `\DeclareMathOperator` as the operators defined call a command `\newmcodes@` which relies on the mathcode of `-` being less than 32768. We delay the definition `\AtBeginDocument` in case `amssymb` hasn't been loaded yet.

```

363 \AtBeginDocument{%
364   \ifx\Umathcode\undefined
365   \gdef\newmcodes@{\mathcode`\'39\mathcode`\*42\mathcode`\."613A%
366   \ifnum\mathcode`-=45 \else

```

The extra check. Don't do anything if `-` is math active.

```

367   \ifnum\mathcode`-=32768\space
368   \else

```

```

369      \mathchardef\std@minus\mathcode`-\relax
370      \fi
371      \fi
372      \mathcode`-45\mathcode`/47\mathcode`:"603A\relax}
373 \else
374 \gdef\newmcodes@{\mathcode`'39\mathcode`*42\mathcode`.".613A%
375 \ifnum\Umathcodenum`=-45 \else

```

The extra check. Don't do anything if - is math active.

```

376 \ifnum\Umathcodenum`=-16777216\space
377 \else
378 \Umathcharnumdef\std@minus\Umathcodenum`-\relax
379 \fi
380 \fi
381 \mathcode`-45\mathcode`/47\mathcode`:"603A\relax}
382 \fi
383 }

```

And we then continue with the options.

```

384 \DeclareOption{mathstyleoff}{%
385   \PassOptionsToPackage{noactivechars}{mathstyle}}
386 \DeclareOption{cmbase}{\usesymbols{cmbase}}
387 \DeclareOption{mathpazo}{\usesymbols{mathpazo}}
388 \DeclareOption{mathptmx}{\usesymbols{mathptmx}}
389 \ExecuteOptions{cmbase}
390 \ProcessOptions\relax
391 \renewcommand{\lnot}{\neg}
392 \renewcommand{\land}{\wedge}
393 \renewcommand{\lor}{\vee}
394 \renewcommand{\le}{\leq}
395 \renewcommand{\ge}{\geq}
396 \renewcommand{\ne}{\neq}
397 \renewcommand{\owns}{\ni}
398 \renewcommand{\gets}{\leftarrow}
399 \renewcommand{\to}{\rightarrow}
400 \renewcommand{\|}{\Vert}
401 \RequirePackage{mathstyle}
402 
```

2 cmbase, mathpazo, mathptmx

For each math font package we define a corresponding symbol file with extension `sym`. The Computer Modern base is called `cmbase` and `mathpazo` and `mathptmx` corresponds to the packages. The definitions are almost identical as they mostly concern the positions in the math font encodings. Look for differences in `\joinord`, `\relbar` and `\Relbar`. If you inspect the source code, you'll see that the support for `mathptmx` didn't require any work but I thought it better to create a `sym` file to maintain a uniform interface.

Open question on ! and ?: maybe they should have type ‘Pun’ instead of ‘DeR’. Need to search for uses in math in AMS archives. Or, maybe add a special ‘Clo’ type for them: non-extensible closing delimiter.

Default mathgroup setup.

```

403 <*cmbase | mathpazo | mathptmx>
404 <cmbase> \ProvidesSymbols{cmbase} [2007/12/19 v0.92]
405 <mathpazo> \ProvidesSymbols{mathpazo} [2010/07/11 v0.3]
406 <mathptmx> \ProvidesSymbols{mathptmx} [2010/07/11 v0.3]
407 \ExplSyntaxOn
408 \cs_gset:cpx {mg@OT1} {\hexnumber@{\symoperators}}
409 \cs_gset:cpx {mg@OML} {\hexnumber@{\symletters}}
410 \cs_gset:cpx {mg@OMS} {\hexnumber@{\symsymbols}}
411 \cs_gset:cpx {mg@OMX} {\hexnumber@{\symlargesymbols}}
412 \cs_gset:Npx \mg@bin {\mg@OMS}
413 \cs_gset:Npx \mg@del {\mg@OMX}
414 \cs_gset:Npx \mg@digit {\exp_not:c{mg@OT1}}
415 \cs_gset:Npn \mg@latin {\mg@OML}
416 \cs_gset_eq:NN \mg@Latin \mg@latin
417 \cs_gset_eq:NN \mg@greek \mg@latin
418 <cmbase | mathptmx> \cs_gset_eq:NN\mg@Greek\mg@digit

```

Mathpazo takes the upper case greeks from the letter font if slantedGreek is in effect, but from *upright* if not. Mathptmx also takes the slanted greek from the letter font.

```

419 <mathpazo> \ifpackagewith{mathpazo}{slantedGreek}{%
420   <mathpazo> \cs_gset_eq:NN\mg@Greek\mg@latin
421   <mathpazo>}%
422   <mathpazo> \cs_gset:cpx{\mg@Greek}{\hexnumber@{\symupright}}
423   <mathpazo>%
424 <mathptmx> \ifpackagewith{mathptmx}{slantedGreek}{%
425   <mathptmx> \cs_gset_eq:NN\mg@Greek\mg@latin
426   <mathptmx>}%
427 \cs_gset_eq:NN \mg@rel \mg@bin
428 \cs_gset_eq:NN \mg@ord \mg@bin
429 \cs_gset_eq:NN \mg@cop \mg@del

```

Symbols from the 128-character **cmr** encoding. Paren and square bracket delimiters from this encoding are covered by the definitions in the **cme** section, however.

```

430 \DeclareFlexSymbol{!} {Pun}{OT1}{21}
431 \DeclareFlexSymbol{+} {Bin}{OT1}{2B}
432 \DeclareFlexSymbol{:} {Rel}{OT1}{3A}
433 \DeclareFlexSymbol{:\colon} {Pun}{OT1}{3A}
434 \DeclareFlexSymbol{;} {Pun}{OT1}{3B}
435 \AtBeginDocument{\DeclareFlexSymbol{=} {Rel}{OT1}{3D}}
436 \DeclareFlexSymbol{?} {Pun}{OT1}{3F}

```

A_MSTEX, and therefore the **amsmath** package, make the uppercase Greek letters class 0 (nonvariable) instead of 7 (variable), to eliminate the glaring inconsistency

with lowercase Greek. (In plain TeX, `\bf\Delta` works, while `\bf\delta` doesn't.) Let us try to make them both variable (fonts permitting) instead of nonvariable.

```

437 \DeclareFlexSymbol{\Gamma}  {Var}{Greek}{00}
438 \DeclareFlexSymbol{\Delta}  {Var}{Greek}{01}
439 \DeclareFlexSymbol{\Theta}  {Var}{Greek}{02}
440 \DeclareFlexSymbol{\Lambda}  {Var}{Greek}{03}
441 \DeclareFlexSymbol{\Xi}    {Var}{Greek}{04}
442 \DeclareFlexSymbol{\Pi}    {Var}{Greek}{05}
443 \DeclareFlexSymbol{\Sigma} {Var}{Greek}{06}
444 \DeclareFlexSymbol{\Upsilon}{Var}{Greek}{07}
445 \DeclareFlexSymbol{\Phi}   {Var}{Greek}{08}
446 \DeclareFlexSymbol{\Psi}   {Var}{Greek}{09}
447 \DeclareFlexSymbol{\Omega} {Var}{Greek}{0A}

```

Decimal digits.

```

448 \DeclareFlexSymbol{0}{Var}{digit}{30}
449 \DeclareFlexSymbol{1}{Var}{digit}{31}
450 \DeclareFlexSymbol{2}{Var}{digit}{32}
451 \DeclareFlexSymbol{3}{Var}{digit}{33}
452 \DeclareFlexSymbol{4}{Var}{digit}{34}
453 \DeclareFlexSymbol{5}{Var}{digit}{35}
454 \DeclareFlexSymbol{6}{Var}{digit}{36}
455 \DeclareFlexSymbol{7}{Var}{digit}{37}
456 \DeclareFlexSymbol{8}{Var}{digit}{38}
457 \DeclareFlexSymbol{9}{Var}{digit}{39}

```

Symbols from the 128-character cmmi encoding.

```

458 \DeclareFlexSymbol{,}{Pun}{OML}{3B}
459 \DeclareFlexSymbol{.}{Ord}{OML}{3A}
460 \DeclareFlexSymbol{/}{Ord}{OML}{3D}
461 \DeclareFlexSymbol{<}{Rel}{OML}{3C}
462 \DeclareFlexSymbol{>}{Rel}{OML}{3E}

```

To do: make the Var property of lc Greek work properly.

```

463 \DeclareFlexSymbol{\alpha}  {Var}{greek}{0B}
464 \DeclareFlexSymbol{\beta}   {Var}{greek}{0C}
465 \DeclareFlexSymbol{\gamma}  {Var}{greek}{0D}
466 \DeclareFlexSymbol{\delta}  {Var}{greek}{0E}
467 \DeclareFlexSymbol{\epsilon} {Var}{greek}{0F}
468 \DeclareFlexSymbol{\zeta}   {Var}{greek}{10}
469 \DeclareFlexSymbol{\eta}    {Var}{greek}{11}
470 \DeclareFlexSymbol{\theta}  {Var}{greek}{12}
471 \DeclareFlexSymbol{\iota}   {Var}{greek}{13}
472 \DeclareFlexSymbol{\kappa}  {Var}{greek}{14}
473 \DeclareFlexSymbol{\lambda} {Var}{greek}{15}
474 \DeclareFlexSymbol{\mu}    {Var}{greek}{16}
475 \DeclareFlexSymbol{\nu}    {Var}{greek}{17}
476 \DeclareFlexSymbol{\xi}    {Var}{greek}{18}
477 \DeclareFlexSymbol{\pi}    {Var}{greek}{19}
478 \DeclareFlexSymbol{\rho}   {Var}{greek}{1A}

```

```

479 \DeclareFlexSymbol{\sigma}      {Var}{greek}{1B}
480 \DeclareFlexSymbol{\tau}        {Var}{greek}{1C}
481 \DeclareFlexSymbol{\upsilon}    {Var}{greek}{1D}
482 \DeclareFlexSymbol{\phi}       {Var}{greek}{1E}
483 \DeclareFlexSymbol{\chi}       {Var}{greek}{1F}
484 \DeclareFlexSymbol{\psi}       {Var}{greek}{20}
485 \DeclareFlexSymbol{\omega}     {Var}{greek}{21}
486 \DeclareFlexSymbol{\varepsilon}   {Var}{greek}{22}
487 \DeclareFlexSymbol{\vartheta}   {Var}{greek}{23}
488 \DeclareFlexSymbol{\varpi}     {Var}{greek}{24}
489 \DeclareFlexSymbol{\varrho}     {Var}{greek}{25}
490 \DeclareFlexSymbol{\varsigma}   {Var}{greek}{26}
491 \DeclareFlexSymbol{\varphi}     {Var}{greek}{27}

```

Note that in plain TeX `\imath` and `\jmath` are not variable-font. But if a `j` changes font to, let's say, sans serif or calligraphic, a dotless `j` in the same context should change font in the same way.

```

492 \DeclareFlexSymbol{\imath}      {Var}{OML}{7B}
493 \DeclareFlexSymbol{\jmath}       {Var}{OML}{7C}
494 \DeclareFlexSymbol{\ell}        {Ord}{OML}{60}
495 \DeclareFlexSymbol{\wp}        {Ord}{OML}{7D}
496 \DeclareFlexSymbol{\partial}    {Ord}{OML}{40}
497 \DeclareFlexSymbol{\flat}      {Ord}{OML}{5B}
498 \DeclareFlexSymbol{\natural}   {Ord}{OML}{5C}
499 \DeclareFlexSymbol{\sharp}     {Ord}{OML}{5D}
500 \DeclareFlexSymbol{\triangleleft} {Bin}{OML}{2F}
501 \DeclareFlexSymbol{\triangleright} {Bin}{OML}{2E}
502 \DeclareFlexSymbol{\star}      {Bin}{OML}{3F}
503 \DeclareFlexSymbol{\smile}     {Rel}{OML}{5E}
504 \DeclareFlexSymbol{\frown}     {Rel}{OML}{5F}
505 \DeclareFlexSymbol{\leftharpoonup} {Rel}{OML}{28}
506 \DeclareFlexSymbol{\leftharpoondown} {Rel}{OML}{29}
507 \DeclareFlexSymbol{\rightharpoonup} {Rel}{OML}{2A}
508 \DeclareFlexSymbol{\rightharpoondown} {Rel}{OML}{2B}

```

Latin

```

509 \DeclareFlexSymbol{a}{Var}{latin}{61}
510 \DeclareFlexSymbol{b}{Var}{latin}{62}
511 \DeclareFlexSymbol{c}{Var}{latin}{63}
512 \DeclareFlexSymbol{d}{Var}{latin}{64}
513 \DeclareFlexSymbol{e}{Var}{latin}{65}
514 \DeclareFlexSymbol{f}{Var}{latin}{66}
515 \DeclareFlexSymbol{g}{Var}{latin}{67}
516 \DeclareFlexSymbol{h}{Var}{latin}{68}
517 \DeclareFlexSymbol{i}{Var}{latin}{69}
518 \DeclareFlexSymbol{j}{Var}{latin}{6A}
519 \DeclareFlexSymbol{k}{Var}{latin}{6B}
520 \DeclareFlexSymbol{l}{Var}{latin}{6C}
521 \DeclareFlexSymbol{m}{Var}{latin}{6D}
522 \DeclareFlexSymbol{n}{Var}{latin}{6E}

```

```

523 \DeclareFlexSymbol{o}{Var}{latin}{6F}
524 \DeclareFlexSymbol{p}{Var}{latin}{70}
525 \DeclareFlexSymbol{q}{Var}{latin}{71}
526 \DeclareFlexSymbol{r}{Var}{latin}{72}
527 \DeclareFlexSymbol{s}{Var}{latin}{73}
528 \DeclareFlexSymbol{t}{Var}{latin}{74}
529 \DeclareFlexSymbol{u}{Var}{latin}{75}
530 \DeclareFlexSymbol{v}{Var}{latin}{76}
531 \DeclareFlexSymbol{w}{Var}{latin}{77}
532 \DeclareFlexSymbol{x}{Var}{latin}{78}
533 \DeclareFlexSymbol{y}{Var}{latin}{79}
534 \DeclareFlexSymbol{z}{Var}{latin}{7A}
535 \DeclareFlexSymbol{A}{Var}{Latin}{41}
536 \DeclareFlexSymbol{B}{Var}{Latin}{42}
537 \DeclareFlexSymbol{C}{Var}{Latin}{43}
538 \DeclareFlexSymbol{D}{Var}{Latin}{44}
539 \DeclareFlexSymbol{E}{Var}{Latin}{45}
540 \DeclareFlexSymbol{F}{Var}{Latin}{46}
541 \DeclareFlexSymbol{G}{Var}{Latin}{47}
542 \DeclareFlexSymbol{H}{Var}{Latin}{48}
543 \DeclareFlexSymbol{I}{Var}{Latin}{49}
544 \DeclareFlexSymbol{J}{Var}{Latin}{4A}
545 \DeclareFlexSymbol{K}{Var}{Latin}{4B}
546 \DeclareFlexSymbol{L}{Var}{Latin}{4C}
547 \DeclareFlexSymbol{M}{Var}{Latin}{4D}
548 \DeclareFlexSymbol{N}{Var}{Latin}{4E}
549 \DeclareFlexSymbol{O}{Var}{Latin}{4F}
550 \DeclareFlexSymbol{P}{Var}{Latin}{50}
551 \DeclareFlexSymbol{Q}{Var}{Latin}{51}
552 \DeclareFlexSymbol{R}{Var}{Latin}{52}
553 \DeclareFlexSymbol{S}{Var}{Latin}{53}
554 \DeclareFlexSymbol{T}{Var}{Latin}{54}
555 \DeclareFlexSymbol{U}{Var}{Latin}{55}
556 \DeclareFlexSymbol{V}{Var}{Latin}{56}
557 \DeclareFlexSymbol{W}{Var}{Latin}{57}
558 \DeclareFlexSymbol{X}{Var}{Latin}{58}
559 \DeclareFlexSymbol{Y}{Var}{Latin}{59}
560 \DeclareFlexSymbol{Z}{Var}{Latin}{5A}

```

The `\ldotpun` glyph is used in constructing the `\ldots` symbol. It is just a period with a different math symbol class. `\lhookRel` and `\rhookRel` are used in a similar way for building hooked arrow symbols.

```

561 \DeclareFlexSymbol{\ldotpun}{Pun}{OML}{3A}
562 \def\ldotp{\ldotpun}
563 \DeclareFlexSymbol{\lhookRel}{Rel}{OML}{2C}
564 \DeclareFlexSymbol{\rhookRel}{Rel}{OML}{2D}

```

Symbols from the 128-character `cmsy` encoding.

```

565 \DeclareFlexSymbol{*-} {Bin}{bin}{03} % \ast
566 \AtBeginDocument{\DeclareFlexSymbol{-} {Bin}{bin}{00}}

```

```

567 \DeclareFlexSymbol{}{} {Ord}{OMS}{6A}
568 \DeclareFlexSymbol{\aleph}{}{} {Ord}{ord}{40}
569 \DeclareFlexSymbol{\Re}{}{} {Ord}{ord}{3C}
570 \DeclareFlexSymbol{\Im}{}{} {Ord}{ord}{3D}
571 \DeclareFlexSymbol{\infty}{}{} {Ord}{ord}{31}
572 \DeclareFlexSymbol{\prime}{}{} {Ord}{ord}{30}
573 \DeclareFlexSymbol{\emptyset}{}{} {Ord}{ord}{3B}
574 \DeclareFlexSymbol{\nabla}{}{} {Ord}{ord}{72}
575 \DeclareFlexSymbol{\top}{}{} {Ord}{ord}{3E}
576 \DeclareFlexSymbol{\bot}{}{} {Ord}{ord}{3F}
577 \DeclareFlexSymbol{\triangle}{}{} {Ord}{ord}{34}
578 \DeclareFlexSymbol{\forall}{}{} {Ord}{ord}{38}
579 \DeclareFlexSymbol{\exists}{}{} {Ord}{ord}{39}
580 \DeclareFlexSymbol{\neg}{}{} {Ord}{ord}{3A}
581 \DeclareFlexSymbol{\clubsuit}{}{} {Ord}{ord}{7C}
582 \DeclareFlexSymbol{\diamondsuit}{}{} {Ord}{ord}{7D}
583 \DeclareFlexSymbol{\heartsuit}{}{} {Ord}{ord}{7E}
584 \DeclareFlexSymbol{\spadesuit}{}{} {Ord}{ord}{7F}
585 \DeclareFlexSymbol{\smallint}{}{} {COs}{OMS}{73}

```

Binary operators.

```

586 \DeclareFlexSymbol{\bigtriangleup}{}{} {Bin}{bin}{34}
587 \DeclareFlexSymbol{\bigtriangledown}{}{} {Bin}{bin}{35}
588 \DeclareFlexSymbol{\wedge}{}{} {Bin}{bin}{5E}
589 \DeclareFlexSymbol{\vee}{}{} {Bin}{bin}{5F}
590 \DeclareFlexSymbol{\cap}{}{} {Bin}{bin}{5C}
591 \DeclareFlexSymbol{\cup}{}{} {Bin}{bin}{5B}
592 \DeclareFlexSymbol{\ddagger}{}{} {Bin}{bin}{7A}
593 \DeclareFlexSymbol{\dagger}{}{} {Bin}{bin}{79}
594 \DeclareFlexSymbol{\sqcap}{}{} {Bin}{bin}{75}
595 \DeclareFlexSymbol{\sqcup}{}{} {Bin}{bin}{74}
596 \DeclareFlexSymbol{\uplus}{}{} {Bin}{bin}{5D}
597 \DeclareFlexSymbol{\amalg}{}{} {Bin}{bin}{71}
598 \DeclareFlexSymbol{\diamond}{}{} {Bin}{bin}{05}
599 \DeclareFlexSymbol{\bullet}{}{} {Bin}{bin}{0F}
600 \DeclareFlexSymbol{\wr}{}{} {Bin}{bin}{6F}
601 \DeclareFlexSymbol{\div}{}{} {Bin}{bin}{04}
602 \DeclareFlexSymbol{\odot}{}{} {Bin}{bin}{0C}
603 \DeclareFlexSymbol{\oslash}{}{} {Bin}{bin}{0B}
604 \DeclareFlexSymbol{\otimes}{}{} {Bin}{bin}{0A}
605 \DeclareFlexSymbol{\ominus}{}{} {Bin}{bin}{09}
606 \DeclareFlexSymbol{\oplus}{}{} {Bin}{bin}{08}
607 \DeclareFlexSymbol{\mp}{}{} {Bin}{bin}{07}
608 \DeclareFlexSymbol{\pm}{}{} {Bin}{bin}{06}
609 \DeclareFlexSymbol{\circ}{}{} {Bin}{bin}{0E}
610 \DeclareFlexSymbol{\bigcirc}{}{} {Bin}{bin}{0D}
611 \DeclareFlexSymbol{\setminus}{}{} {Bin}{bin}{6E}
612 \DeclareFlexSymbol{\cdotp}{}{} {Bin}{bin}{01}
613 \DeclareFlexSymbol{\ast}{}{} {Bin}{bin}{03}
614 \DeclareFlexSymbol{\times}{}{} {Bin}{bin}{02}

```

Relation symbols.

```

615 \DeclareFlexSymbol{\propto}          {Rel}{rel}{2F}
616 \DeclareFlexSymbol{\sqsubseteqq}       {Rel}{rel}{76}
617 \DeclareFlexSymbol{\sqsupseteqq}       {Rel}{rel}{77}
618 \DeclareFlexSymbol{\parallel}         {Rel}{rel}{6B}
619 \DeclareFlexSymbol{\mid}              {Rel}{rel}{6A}
620 \DeclareFlexSymbol{\dashv}            {Rel}{rel}{61}
621 \DeclareFlexSymbol{\vdash}            {Rel}{rel}{60}
622 \DeclareFlexSymbol{\nearrow}          {Rel}{rel}{25}
623 \DeclareFlexSymbol{\searrow}          {Rel}{rel}{26}
624 \DeclareFlexSymbol{\nwarrow}          {Rel}{rel}{2D}
625 \DeclareFlexSymbol{\swarrow}          {Rel}{rel}{2E}
626 \DeclareFlexSymbol{\Leftrightarrow}{Rel}{rel}{2C}
627 \DeclareFlexSymbol{\Leftarrow}         {Rel}{rel}{28}
628 \DeclareFlexSymbol{\Rightarrow}        {Rel}{rel}{29}
629 \DeclareFlexSymbol{\leq}              {Rel}{rel}{14}
630 \DeclareFlexSymbol{\geq}              {Rel}{rel}{15}
631 \DeclareFlexSymbol{\succ}             {Rel}{rel}{1F}
632 \DeclareFlexSymbol{\prec}             {Rel}{rel}{1E}
633 \DeclareFlexSymbol{\approx}           {Rel}{rel}{19}
634 \DeclareFlexSymbol{\succeq}           {Rel}{rel}{17}
635 \DeclareFlexSymbol{\preceq}           {Rel}{rel}{16}
636 \DeclareFlexSymbol{\supset}            {Rel}{rel}{1B}
637 \DeclareFlexSymbol{\subset}            {Rel}{rel}{1A}
638 \DeclareFlexSymbol{\supseteqq}         {Rel}{rel}{13}
639 \DeclareFlexSymbol{\subsetneqq}         {Rel}{rel}{12}
640 \DeclareFlexSymbol{\in}               {Rel}{rel}{32}
641 \DeclareFlexSymbol{\ni}               {Rel}{rel}{33}
642 \DeclareFlexSymbol{\gg}               {Rel}{rel}{1D}
643 \DeclareFlexSymbol{\ll}               {Rel}{rel}{1C}
644 \DeclareFlexSymbol{\Leftrightarrow}{Rel}{rel}{24}
645 \DeclareFlexSymbol{\Leftarrow}         {Rel}{rel}{20}
646 \DeclareFlexSymbol{\Rightarrow}        {Rel}{rel}{21}
647 \DeclareFlexSymbol{\sim}              {Rel}{rel}{18}
648 \DeclareFlexSymbol{\simeq}             {Rel}{rel}{27}
649 \DeclareFlexSymbol{\perp}              {Rel}{rel}{3F}
650 \DeclareFlexSymbol{\equiv}             {Rel}{rel}{11}
651 \DeclareFlexSymbol{\asymp}            {Rel}{rel}{10}

```

The `\notRel` glyph is a special zero-width glyph intended only for use in constructing negated symbols. `\mapstoRel` and `\cdotPun` have similar but more restricted applications.

```

652 \DeclareFlexSymbol{\notRel}           {Rel}{rel}{36}
653 \DeclareFlexSymbol{\mapstoOrd}{Ord}{OMS}{37}
654 \DeclareFlexSymbol{\cdotOrd}          {Ord}{OMS}{01}
655 \cs_set:Npn\cdotPun{\mathpunct{\cdotOrd}}

```

Symbols from the 128-character `cmex` encoding. `C0s` stands for ‘cumulative operator (sum-like)’. `C0i` stands for ‘cumulative operator (integral-like)’. These typically differ only in the default placement of limits. `cop` stands for ‘cumulative

operator math group'.

```

656 \DeclareFlexSymbol{\coprod} {C0s}{cop}{60}
657 \DeclareFlexSymbol{\bigvee} {C0s}{cop}{57}
658 \DeclareFlexSymbol{\bigwedge} {C0s}{cop}{56}
659 \DeclareFlexSymbol{\biguplus} {C0s}{cop}{55}
660 \DeclareFlexSymbol{\bigcap} {C0s}{cop}{54}
661 \DeclareFlexSymbol{\bigcup} {C0s}{cop}{53}
662 \DeclareFlexSymbol{\int} {C0i}{cop}{52}
663 \DeclareFlexSymbol{\prod} {C0s}{cop}{51}
664 \DeclareFlexSymbol{\sum} {C0s}{cop}{50}
665 \DeclareFlexSymbol{\bigotimes}{C0s}{cop}{4E}
666 \DeclareFlexSymbol{\bigoplus} {C0s}{cop}{4C}
667 \DeclareFlexSymbol{\bigodot} {C0s}{cop}{4A}
668 \DeclareFlexSymbol{\oint} {C0i}{cop}{48}
669 \DeclareFlexSymbol{\bigsqcup} {C0s}{cop}{46}

```

Delimiter symbols. DeL stands for ‘delimiter (left)’. DeR stands for ‘delimiter (right)’. DeB stands for ‘delimiter (bidirectional)’. The principal encoding point for an extensible delimiter is the first link in the list of linked sizes as specified in the font metric information. For a math encoding such as OT1/OML/OMS/OMX where not all sizes of a given delimiter reside in a given font, the extra encoding point for the smallest delimiter must be supplied by defining

\sd@GXX

where G is the mathgroup and XX is the hexadecimal glyph position. \DeclareFlexDelimiter does that for us.

```

670 \DeclareFlexDelimiter{\rangle}{DeR}{del}{0B}{OMS}{69}
671 \DeclareFlexDelimiter{\langle}{DeL}{del}{0A}{OMS}{68}
672 \DeclareFlexDelimiter{\rbrace}{DeR}{del}{09}{OMS}{67}
673 \DeclareFlexDelimiter{\lbrace}{DeL}{del}{08}{OMS}{66}
674 \DeclareFlexDelimiter{\rcceil}{DeR}{del}{07}{OMS}{65}
675 \DeclareFlexDelimiter{\lceil}{DeL}{del}{06}{OMS}{64}
676 \DeclareFlexDelimiter{\rfloor}{DeR}{del}{05}{OMS}{63}
677 \DeclareFlexDelimiter{\lfloor}{DeL}{del}{04}{OMS}{62}
678 \DeclareFlexDelimiter{\{}{DeL}{del}{00}{OT1}{28}
679 \DeclareFlexDelimiter{\}}{DeR}{del}{01}{OT1}{29}
680 \DeclareFlexDelimiter{\[]}{DeL}{del}{02}{OT1}{5B}
681 \DeclareFlexDelimiter{\]}{DeR}{del}{03}{OT1}{5D}
682 \DeclareFlexDelimiter{\lVert}{DeL}{del}{0D}{OMS}{6B}
683 \DeclareFlexDelimiter{\rVert}{DeR}{del}{0D}{OMS}{6B}
684 \DeclareFlexDelimiter{\lvert}{DeL}{del}{0C}{OMS}{6A}
685 \DeclareFlexDelimiter{\rvert}{DeR}{del}{0C}{OMS}{6A}
686 \DeclareFlexDelimiter{\Vert}{DeB}{del}{0D}{OMS}{6B}
687 \DeclareFlexDelimiter{\vert}{DeB}{del}{0C}{OMS}{6A}

```

Maybe make the vert bars mathord instead of delimiter, to discourage poor usage.

```

688 \DeclareFlexDelimiter{|}{DeB}{del}{0C}{OMS}{6A}
689 \DeclareFlexDelimiter{/}{DeB}{del}{0E}{OML}{3D}

```

These wacky delimiters need to be supported I guess for compatibility reasons. The DeA delimiter type is a special case used only for these arrows.

```

690 \DeclareFlexDelimiter{\lmoustache} {DeL}{del}{40}{del}{7A}
691 \DeclareFlexDelimiter{\rmoustache} {DeR}{del}{41}{del}{7B}
692 \DeclareFlexDelimiter{\lgroup} {DeL}{del}{3A}{del}{3A}
693 \DeclareFlexDelimiter{\rgroup} {DeR}{del}{3B}{del}{3B}
694 \DeclareFlexDelimiter{\bracevert} {DeB}{del}{3E}{del}{3E}
695 \DeclareFlexDelimiter{\arrowvert} {DeB}{del}{3C}{OMS}{6A}
696 \DeclareFlexDelimiter{\Arrowvert} {DeB}{del}{3D}{OMS}{6B}
697 \DeclareFlexDelimiter{\uparrow} {DeA}{del}{78}{OMS}{22}
698 \DeclareFlexDelimiter{\downarrow} {DeA}{del}{79}{OMS}{23}
699 \DeclareFlexDelimiter{\updownarrow}{DeA}{del}{3F}{OMS}{6C}
700 \DeclareFlexDelimiter{\Uparrow} {DeA}{del}{7E}{OMS}{2A}
701 \DeclareFlexDelimiter{\Downarrow} {DeA}{del}{7F}{OMS}{2B}
702 \DeclareFlexDelimiter{\Updownarrow}{DeA}{del}{77}{OMS}{6D}
703 \DeclareFlexDelimiter{\backslash} {DeB}{del}{0F}{OMS}{6E}
```

3 Some compound symbols

The following symbols are not robust in standard L^AT_EX because they use # or \mathpalette (which is not robust and contains a # in its expansion): \angle, \cong, \notin, \rightleftharpoons.

In this definition of \hbar, the symbol is cobbled together from a math italic h and the cmr overbar accent glyph.

```

704 \DeclareFlexSymbol{\hbarOrd}{0rd}{OT1}{16}
705 \DeclareFlexCompoundSymbol{\hbar}{0rd}{\hbarOrd\mkern-9mu h}
```

For \surd, the interior symbol gets math class 1 (cumulative operator) to make the glyph vertically centered on the math axis, but the desired horizontal spacing is the spacing for a mathord. (Couldn't it just be class mathopen, though?)

```

706 \DeclareFlexSymbol{\surdOrd}{0rd}{OMS}{70}
707 \DeclareFlexCompoundSymbol{\surd}{0rd}{\mathop{\surdOrd}}
```

As shown in this definition of \angle, rule dimens are not allowed to use mathunits, unfortunately.

```

708 \DeclareFlexCompoundSymbol{\angle}{0rd}{%
709   \vbox{\ialign{%
710     $ \mathrel{\scriptstyle##\$} \cr
711     \notRel \mathrel{\mkern14mu} \cr
712     \noalign{\nointerlineskip}%
713     \mkern2.5mu \leaders\hrule \height.34pt \hfill \mkern2.5mu \cr
714   }%
715 }}
```

The \not function, which is defined in the flexisym package, requires a suitably defined \notRel symbol.

```
716 \DeclareFlexCompoundSymbol{\neq}{Rel}{\not{=}}
```

```

717 \DeclareFlexCompoundSymbol{\mapsto}{\Rel}{\mapstoOrd\rightarrowarrow}

The \ vereq function ends by centering the whole construction on the math axis,
unlike \ buildrel where the base symbol remains at its normal altitude. Furthermore, \ vereq leaves the math style of the top symbol as given instead of
downsizing to scriptstyle.

718 \DeclareFlexCompoundSymbol{\cong}{\Rel}{\mathpalette\@req\sim}

The \m@th in the fontmath.ltx definition of \notin is superfluous unless \c@ncel
doesn't include it (which was perhaps true in an older version of plain.tex?).

719 \providecommand*\joinord{}

720 <cmbase | mathptmx> \renewcommand*\joinord{\mkern-3mu }

721 <mathpazo> \renewcommand*\joinord{\mkern-3.45mu }

722 \DeclareFlexCompoundSymbol{\notin}{\Rel}{\mathpalette\c@ncel\in}

723 \DeclareFlexCompoundSymbol{\rightleftharpoons}{\Rel}{\mathpalette\rlh@{}}

724 \DeclareFlexCompoundSymbol{\doteq}{\Rel}{\buildrel\textstyle.\over=}

725 \DeclareFlexCompoundSymbol{\hookrightarrow}{\Rel}{\lhook\relax\joinord\rightarrowarrow}

726 \DeclareFlexCompoundSymbol{\hookleftarrow}{\Rel}{\leftarrow\relax\joinord\rhook\relax}

727 \DeclareFlexCompoundSymbol{\bowtie}{\Rel}{\triangleright\joinord\triangleleft}

728 \DeclareFlexCompoundSymbol{\models}{\Rel}{\vert\joinord=}

729 \DeclareFlexCompoundSymbol{\Longrightarrow}{\Rel}{\relbar\joinord\rightarrowarrow}

730 \DeclareFlexCompoundSymbol{\longrightarrow}{\Rel}{\relbar\joinord\rightarrow}

731 \DeclareFlexCompoundSymbol{\Longleftarrow}{\Rel}{\leftarrow\joinord\relbar}

732 \DeclareFlexCompoundSymbol{\longleftarrow}{\Rel}{\leftarrow\joinord\relbar}

733 \DeclareFlexCompoundSymbol{\longmapsto}{\Rel}{\mapstochar\longrightarrow}

734 \DeclareFlexCompoundSymbol{\longleftrightarrow}{\Rel}{\leftarrow\joinord\rightarrow}

735 \DeclareFlexCompoundSymbol{\Longleftrightarrow}{\Rel}{\Leftarrow\joinord\rightarrowarrow}

```

Here is what you get from the old definition of \iff.

```

\glue 2.77771 plus 2.77771
\glue(\thickmuskip) 2.77771 plus 2.77771
\OMS/cmsy/m/n/10 (
\hbox(0.0+0.0)x-1.66663
.\kern -1.66663
\OMS/cmsy/m/n/10 )
\penalty 500
\glue 2.77771 plus 2.77771
\glue(\thickmuskip) 2.77771 plus 2.77771

```

Looks like it could be simplified slightly. But it's not so easy as it looks to do it without screwing up the line breaking possibilities.

```

736 \renewcommand*\iff{%
737   \mskip\thickmuskip\Longleftrightarrow\mskip\thickmuskip
738 }

```

Some dotly symbols.

```

739 \DeclareFlexCompoundSymbol{\cdots}{\Inn}{\cdotp\cdotp\cdotp}%
740 \DeclareFlexCompoundSymbol{\vdots}{\Ord}{\%

```

```

741   \vbox{\baselineskip4\p@ \lineskiplimit\z@
742     \kern6\p@\hbox{.}\hbox{.}\hbox{.}}}
743 \DeclareFlexCompoundSymbol{\ddots}{Inn}{%
744   \mkern1mu\raise7\p@%
745   \vbox{\kern7\p@\hbox{.}}\mkern2mu%
746   \raise4\p@\hbox{.}\mkern2mu\raise\p@\hbox{.}\mkern1mu%
747 }
.
```

748 \def\relbar{\begingroup \def\smash@{tb}%
749 \mathpalette\mathsm@sh{\mathchar"200 }\endgroup}

For \Relbar we take an equal sign of class 0 (Ord) from the operator family. For cmr and mathptmx we know this is family 0.

750 <cmbase | mathptmx> \def\Relbar{\mathchar"3D }

For the mathpazo setup we need to use the equal sign from cmr and so must insert class 0 and use the symbol from the upright symbols.

751 <mathpazo> \edef\Relbar{\mathchar\$string"\hexnumber@\symupright3D }

Done.

```

752 \ExplSyntaxOff
753 </cmbase | mathpazo | mathptmx>
```

Various synonyms such as \leq for \leq and \to for \rightarrow are defined in flexisym with \def instead of \let, for slower execution speed but smaller chance of synchronization problems.

```

754 <*msabm>
755 \ProvidesSymbols{msabm}[2001/09/08 v0.91]
756 \ExplSyntaxOn
757 \RequirePackage{amsfonts}\relax
758 \cs_gset:cpx{mg@MSA}{\hexnumber@\symAMSA}%
759 \cs_gset:cpx{mg@MSB}{\hexnumber@\symAMSB}%
760 \DeclareFlexSymbol{\boxdot} {Bin}{MSA}{00}
761 \DeclareFlexSymbol{\boxplus} {Bin}{MSA}{01}
762 \DeclareFlexSymbol{\boxtimes} {Bin}{MSA}{02}
763 \DeclareFlexSymbol{\square} {Ord}{MSA}{03}
764 \DeclareFlexSymbol{\blacksquare} {Ord}{MSA}{04}
765 \DeclareFlexSymbol{\centerdot} {Bin}{MSA}{05}
766 \DeclareFlexSymbol{\lozenge} {Ord}{MSA}{06}
767 \DeclareFlexSymbol{\blacklozenge} {Ord}{MSA}{07}
768 \DeclareFlexSymbol{\circlearrowright} {Rel}{MSA}{08}
769 \DeclareFlexSymbol{\circlearrowleft} {Rel}{MSA}{09}
```

In amsfonts.sty:

```

770 \% \DeclareFlexSymbol{\rightleftharpoons}{Rel}{MSA}{0A}
771 \DeclareFlexSymbol{\leftrightharpoons} {Rel}{MSA}{0B}
772 \DeclareFlexSymbol{\boxminus} {Bin}{MSA}{0C}
773 \DeclareFlexSymbol{\Vdash} {Rel}{MSA}{0D}
774 \DeclareFlexSymbol{\Vvdash} {Rel}{MSA}{0E}
```

```

775 \DeclareFlexSymbol{\vDash} {Rel}{MSA}{OF}
776 \DeclareFlexSymbol{\twoheadrightarrow} {Rel}{MSA}{10}
777 \DeclareFlexSymbol{\twoheadleftarrow} {Rel}{MSA}{11}
778 \DeclareFlexSymbol{\leftleftarrows} {Rel}{MSA}{12}
779 \DeclareFlexSymbol{\rightrightarrows} {Rel}{MSA}{13}
780 \DeclareFlexSymbol{\upuparrows} {Rel}{MSA}{14}
781 \DeclareFlexSymbol{\downdownarrows} {Rel}{MSA}{15}
782 \DeclareFlexSymbol{\upharpoonright} {Rel}{MSA}{16}
783 \let\restriction\upharpoonright
784 \DeclareFlexSymbol{\downharpoonright} {Rel}{MSA}{17}
785 \DeclareFlexSymbol{\upharpoonleft} {Rel}{MSA}{18}
786 \DeclareFlexSymbol{\downharpoonleft} {Rel}{MSA}{19}
787 \DeclareFlexSymbol{\rightarrowtail} {Rel}{MSA}{1A}
788 \DeclareFlexSymbol{\leftarrowtail} {Rel}{MSA}{1B}
789 \DeclareFlexSymbol{\leftrightsquigarrow} {Rel}{MSA}{1C}
790 \DeclareFlexSymbol{\rightleftarrows} {Rel}{MSA}{1D}
791 \DeclareFlexSymbol{\Lsh} {Rel}{MSA}{1E}
792 \DeclareFlexSymbol{\Rsh} {Rel}{MSA}{1F}
793 \DeclareFlexSymbol{\rightsquigarrow} {Rel}{MSA}{20}
794 \DeclareFlexSymbol{\leftrightsquigarrow} {Rel}{MSA}{21}
795 \DeclareFlexSymbol{\looparrowleft} {Rel}{MSA}{22}
796 \DeclareFlexSymbol{\looparrowright} {Rel}{MSA}{23}
797 \DeclareFlexSymbol{\circeq} {Rel}{MSA}{24}
798 \DeclareFlexSymbol{\succsim} {Rel}{MSA}{25}
799 \DeclareFlexSymbol{\gtrsim} {Rel}{MSA}{26}
800 \DeclareFlexSymbol{\gtrapprox} {Rel}{MSA}{27}
801 \DeclareFlexSymbol{\multimap} {Rel}{MSA}{28}
802 \DeclareFlexSymbol{\therefore} {Rel}{MSA}{29}
803 \DeclareFlexSymbol{\because} {Rel}{MSA}{2A}
804 \DeclareFlexSymbol{\doteqdot} {Rel}{MSA}{2B}
805 \let\Doteq\doteqdot
806 \DeclareFlexSymbol{\triangleq} {Rel}{MSA}{2C}
807 \DeclareFlexSymbol{\precsim} {Rel}{MSA}{2D}
808 \DeclareFlexSymbol{\lessim} {Rel}{MSA}{2E}
809 \DeclareFlexSymbol{\lessapprox} {Rel}{MSA}{2F}
810 \DeclareFlexSymbol{\eqslantless} {Rel}{MSA}{30}
811 \DeclareFlexSymbol{\eqslantgr} {Rel}{MSA}{31}
812 \DeclareFlexSymbol{\curlyeqprec} {Rel}{MSA}{32}
813 \DeclareFlexSymbol{\curlyeqsucc} {Rel}{MSA}{33}
814 \DeclareFlexSymbol{\preccurlyeq} {Rel}{MSA}{34}
815 \DeclareFlexSymbol{\leqq} {Rel}{MSA}{35}
816 \DeclareFlexSymbol{\leqslant} {Rel}{MSA}{36}
817 \DeclareFlexSymbol{\lessgtr} {Rel}{MSA}{37}
818 \DeclareFlexSymbol{\backprime} {Ord}{MSA}{38}
819 \DeclareFlexSymbol{\risingdotseq} {Rel}{MSA}{3A}
820 \DeclareFlexSymbol{\fallingdotseq} {Rel}{MSA}{3B}
821 \DeclareFlexSymbol{\succcurlyeq} {Rel}{MSA}{3C}
822 \DeclareFlexSymbol{\geqq} {Rel}{MSA}{3D}
823 \DeclareFlexSymbol{\geqslant} {Rel}{MSA}{3E}
824 \DeclareFlexSymbol{\gtrless} {Rel}{MSA}{3F}

```

in amsfonts.sty

```
825 %% \DeclareFlexSymbol{\sqsubset}{\relax}{MSA}{40}
826 %% \DeclareFlexSymbol{\sqsupset}{\relax}{MSA}{41}
827 \DeclareFlexSymbol{\vartriangleright}{\relax}{MSA}{42}
828 \DeclareFlexSymbol{\vartriangleleft}{\relax}{MSA}{43}
829 \DeclareFlexSymbol{\trianglerighteq}{\relax}{MSA}{44}
830 \DeclareFlexSymbol{\trianglelefteq}{\relax}{MSA}{45}
831 \DeclareFlexSymbol{\bigstar}{\relax}{MSA}{46}
832 \DeclareFlexSymbol{\between}{\relax}{MSA}{47}
833 \DeclareFlexSymbol{\blacktriangledown}{\relax}{MSA}{48}
834 \DeclareFlexSymbol{\blacktriangleright}{\relax}{MSA}{49}
835 \DeclareFlexSymbol{\blacktriangleleft}{\relax}{MSA}{4A}
836 \DeclareFlexSymbol{\vartriangle}{\relax}{MSA}{4D}
837 \DeclareFlexSymbol{\blacktriangle}{\relax}{MSA}{4E}
838 \DeclareFlexSymbol{\triangledown}{\relax}{MSA}{4F}
839 \DeclareFlexSymbol{\eqcirc}{\relax}{MSA}{50}
840 \DeclareFlexSymbol{\lesseqgtr}{\relax}{MSA}{51}
841 \DeclareFlexSymbol{\gtreqless}{\relax}{MSA}{52}
842 \DeclareFlexSymbol{\lesseqqgtr}{\relax}{MSA}{53}
843 \DeclareFlexSymbol{\gtreqqless}{\relax}{MSA}{54}
844 \DeclareFlexSymbol{\rightarrowarrow}{\relax}{MSA}{56}
845 \DeclareFlexSymbol{\leftarrowarrow}{\relax}{MSA}{57}
846 \DeclareFlexSymbol{\veebar}{\relax}{MSA}{59}
847 \DeclareFlexSymbol{\barwedge}{\relax}{MSA}{5A}
848 \DeclareFlexSymbol{\doublebarwedge}{\relax}{MSA}{5B}
```

In amsfonts.sty

```
849 %% \DeclareFlexSymbol{\angle}{\relax}{MSA}{5C}
850 \DeclareFlexSymbol{\measuredangle}{\relax}{MSA}{5D}
851 \DeclareFlexSymbol{\sphericalangle}{\relax}{MSA}{5E}
852 \DeclareFlexSymbol{\varpropto}{\relax}{MSA}{5F}
853 \DeclareFlexSymbol{\smallsmile}{\relax}{MSA}{60}
854 \DeclareFlexSymbol{\smallfrown}{\relax}{MSA}{61}
855 \DeclareFlexSymbol{\Subset}{\relax}{MSA}{62}
856 \DeclareFlexSymbol{\Supset}{\relax}{MSA}{63}
857 \DeclareFlexSymbol{\Cup}{\relax}{MSA}{64}
858 \let\doublecup\Cup
859 \DeclareFlexSymbol{\Cap}{\relax}{MSA}{65}
860 \let\doublecap\Cap
861 \DeclareFlexSymbol{\curlywedge}{\relax}{MSA}{66}
862 \DeclareFlexSymbol{\curlyvee}{\relax}{MSA}{67}
863 \DeclareFlexSymbol{\leftthreetimes}{\relax}{MSA}{68}
864 \DeclareFlexSymbol{\rightthreetimes}{\relax}{MSA}{69}
865 \DeclareFlexSymbol{\subseteqq}{\relax}{MSA}{6A}
866 \DeclareFlexSymbol{\supseteqq}{\relax}{MSA}{6B}
867 \DeclareFlexSymbol{\bumpeq}{\relax}{MSA}{6C}
868 \DeclareFlexSymbol{\Bumpeq}{\relax}{MSA}{6D}
869 \DeclareFlexSymbol{\lll}{\relax}{MSA}{6E}
870 \let\llless\lll
871 \DeclareFlexSymbol{\ggg}{\relax}{MSA}{6F}
```

```

872 \let\gggtr\ggg
873 \DeclareFlexSymbol{\circledS} {Ord}{MSA}{73}
874 \DeclareFlexSymbol{\pitchfork} {Rel}{MSA}{74}
875 \DeclareFlexSymbol{\dotplus}   {Bin}{MSA}{75}
876 \DeclareFlexSymbol{\backsim}  {Rel}{MSA}{76}
877 \DeclareFlexSymbol{\backsimeq} {Rel}{MSA}{77}
878 \DeclareFlexSymbol{\complement} {Ord}{MSA}{7B}
879 \DeclareFlexSymbol{\intercal}  {Bin}{MSA}{7C}
880 \DeclareFlexSymbol{\circledcirc} {Bin}{MSA}{7D}
881 \DeclareFlexSymbol{\circledast}  {Bin}{MSA}{7E}
882 \DeclareFlexSymbol{\circleddash} {Bin}{MSA}{7F}

Begin AMSb declarations
883 \DeclareFlexSymbol{\lvertneqq} {Rel}{MSB}{00}
884 \DeclareFlexSymbol{\gvertneqq} {Rel}{MSB}{01}
885 \DeclareFlexSymbol{\nleq}     {Rel}{MSB}{02}
886 \DeclareFlexSymbol{\ngeq}     {Rel}{MSB}{03}
887 \DeclareFlexSymbol{\nless}    {Rel}{MSB}{04}
888 \DeclareFlexSymbol{\ngtr}    {Rel}{MSB}{05}
889 \DeclareFlexSymbol{\nprec}   {Rel}{MSB}{06}
890 \DeclareFlexSymbol{\nsucc}   {Rel}{MSB}{07}
891 \DeclareFlexSymbol{\lneqq}   {Rel}{MSB}{08}
892 \DeclareFlexSymbol{\gneqq}   {Rel}{MSB}{09}
893 \DeclareFlexSymbol{\nleqslant} {Rel}{MSB}{0A}
894 \DeclareFlexSymbol{\ngeqslant} {Rel}{MSB}{0B}
895 \DeclareFlexSymbol{\lneq}    {Rel}{MSB}{0C}
896 \DeclareFlexSymbol{\gneq}    {Rel}{MSB}{0D}
897 \DeclareFlexSymbol{\npreceq}  {Rel}{MSB}{0E}
898 \DeclareFlexSymbol{\nsucceq}  {Rel}{MSB}{0F}
899 \DeclareFlexSymbol{\precnsim} {Rel}{MSB}{10}
900 \DeclareFlexSymbol{\succnsim} {Rel}{MSB}{11}
901 \DeclareFlexSymbol{\lnsim}   {Rel}{MSB}{12}
902 \DeclareFlexSymbol{\gnsim}   {Rel}{MSB}{13}
903 \DeclareFlexSymbol{\nleqq}   {Rel}{MSB}{14}
904 \DeclareFlexSymbol{\ngeqq}   {Rel}{MSB}{15}
905 \DeclareFlexSymbol{\precneqq} {Rel}{MSB}{16}
906 \DeclareFlexSymbol{\succcneqq} {Rel}{MSB}{17}
907 \DeclareFlexSymbol{\precnapprox} {Rel}{MSB}{18}
908 \DeclareFlexSymbol{\succcnapprox} {Rel}{MSB}{19}
909 \DeclareFlexSymbol{\lnapprox} {Rel}{MSB}{1A}
910 \DeclareFlexSymbol{\gnapprox} {Rel}{MSB}{1B}
911 \DeclareFlexSymbol{\nsim}    {Rel}{MSB}{1C}
912 \DeclareFlexSymbol{\ncong}   {Rel}{MSB}{1D}
913 \DeclareFlexSymbol{\diagup}  {Ord}{MSB}{1E}
914 \DeclareFlexSymbol{\diagdown} {Ord}{MSB}{1F}
915 \DeclareFlexSymbol{\varsubsetneq} {Rel}{MSB}{20}
916 \DeclareFlexSymbol{\varsupsetneq} {Rel}{MSB}{21}
917 \DeclareFlexSymbol{\nsubseteqq} {Rel}{MSB}{22}
918 \DeclareFlexSymbol{\nsupseteqq} {Rel}{MSB}{23}
919 \DeclareFlexSymbol{\subsetneqq} {Rel}{MSB}{24}

```

```

920 \DeclareFlexSymbol{\supsetneqq} {Rel}{MSB}{25}
921 \DeclareFlexSymbol{\varsubsetneqq} {Rel}{MSB}{26}
922 \DeclareFlexSymbol{\varsupsetneqq} {Rel}{MSB}{27}
923 \DeclareFlexSymbol{\subsetneq} {Rel}{MSB}{28}
924 \DeclareFlexSymbol{\supsetneq} {Rel}{MSB}{29}
925 \DeclareFlexSymbol{\nsubseteqq} {Rel}{MSB}{2A}
926 \DeclareFlexSymbol{\nsupseteqq} {Rel}{MSB}{2B}
927 \DeclareFlexSymbol{\nparallel} {Rel}{MSB}{2C}
928 \DeclareFlexSymbol{\nmid} {Rel}{MSB}{2D}
929 \DeclareFlexSymbol{\nshortmid} {Rel}{MSB}{2E}
930 \DeclareFlexSymbol{\nshortparallel} {Rel}{MSB}{2F}
931 \DeclareFlexSymbol{\nvdash} {Rel}{MSB}{30}
932 \DeclareFlexSymbol{\nVdash} {Rel}{MSB}{31}
933 \DeclareFlexSymbol{\nvDash} {Rel}{MSB}{32}
934 \DeclareFlexSymbol{\nVDash} {Rel}{MSB}{33}
935 \DeclareFlexSymbol{\ntrianglerighteq} {Rel}{MSB}{34}
936 \DeclareFlexSymbol{\ntrianglelefteq} {Rel}{MSB}{35}
937 \DeclareFlexSymbol{\ntriangleleft} {Rel}{MSB}{36}
938 \DeclareFlexSymbol{\ntriangleright} {Rel}{MSB}{37}
939 \DeclareFlexSymbol{\nleftarrow} {Rel}{MSB}{38}
940 \DeclareFlexSymbol{\nrightarrow} {Rel}{MSB}{39}
941 \DeclareFlexSymbol{\nLeftarrow} {Rel}{MSB}{3A}
942 \DeclareFlexSymbol{\nRightarrow} {Rel}{MSB}{3B}
943 \DeclareFlexSymbol{\nLeftrightarrow} {Rel}{MSB}{3C}
944 \DeclareFlexSymbol{\nlefrightharpoonup} {Rel}{MSB}{3D}
945 \DeclareFlexSymbol{\divideontimes} {Bin}{MSB}{3E}
946 \DeclareFlexSymbol{\varnothing} {Ord}{MSB}{3F}
947 \DeclareFlexSymbol{\nexists} {Ord}{MSB}{40}
948 \DeclareFlexSymbol{\Finv} {Ord}{MSB}{60}
949 \DeclareFlexSymbol{\Game} {Ord}{MSB}{61}

```

In amsfonts.sty:

```

950 %%\DeclareFlexSymbol{\mho} {Ord}{MSB}{66}
951 \DeclareFlexSymbol{\eth} {Ord}{MSB}{67}
952 \DeclareFlexSymbol{\eqsim} {Rel}{MSB}{68}
953 \DeclareFlexSymbol{\beth} {Ord}{MSB}{69}
954 \DeclareFlexSymbol{\gimel} {Ord}{MSB}{6A}
955 \DeclareFlexSymbol{\daleth} {Ord}{MSB}{6B}
956 \DeclareFlexSymbol{\lessdot} {Bin}{MSB}{6C}
957 \DeclareFlexSymbol{\gtrdot} {Bin}{MSB}{6D}
958 \DeclareFlexSymbol{\ltimes} {Bin}{MSB}{6E}
959 \DeclareFlexSymbol{\rtimes} {Bin}{MSB}{6F}
960 \DeclareFlexSymbol{\shortmid} {Rel}{MSB}{70}
961 \DeclareFlexSymbol{\shortparallel} {Rel}{MSB}{71}
962 \DeclareFlexSymbol{\smallsetminus} {Bin}{MSB}{72}
963 \DeclareFlexSymbol{\thicksim} {Rel}{MSB}{73}
964 \DeclareFlexSymbol{\thickapprox} {Rel}{MSB}{74}
965 \DeclareFlexSymbol{\approxeq} {Rel}{MSB}{75}
966 \DeclareFlexSymbol{\succapprox} {Rel}{MSB}{76}
967 \DeclareFlexSymbol{\precapprox} {Rel}{MSB}{77}

```

```

968 \DeclareFlexSymbol{\curvearrowleft} {Rel}{MSB}{78}
969 \DeclareFlexSymbol{\curvearrowright} {Rel}{MSB}{79}
970 \DeclareFlexSymbol{\digamma} {Ord}{MSB}{7A}
971 \DeclareFlexSymbol{\varkappa} {Ord}{MSB}{7B}
972 \DeclareFlexSymbol{\Bbbk} {Ord}{MSB}{7C}
973 \DeclareFlexSymbol{\hslash} {Ord}{MSB}{7D}

```

In amsfonts.sty:

```

974 %\DeclareFlexSymbol{\hbar} {Ord}{MSB}{7E}
975 \DeclareFlexSymbol{\backepsilon} {Rel}{MSB}{7F}
976 \ExplSyntaxOff
977 
```

Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	
\"	7, 12
\'	365, 374
*	365, 374
\-	366, 367, 369, 372, 375, 376, 378, 381
\.	349, 365, 374
\/	372, 381
\:	372, 381
\@firstofone	100
\@gobble	13, 346
\@gobblethree	328
\@height	713
\@ifpackageloaded	361
\@ifpackagewith	419, 424
\@ifundefined	284, 290
\@nil	347, 350
\@onefilewithoptions	335
\@sym	13, 15, 94, 229, 255, 264, 329, 344
\@sym@ord	344, 347
\@sym@ord@a	347, 350
\@symAcc	94
\@symBin	85
\@symCOi	88
\@symCOs	89
\@symDeA	93
\@symDeB	92
\@symDeL	90
\@symDeR	91
\@symErr	313
\@symOrd	83
\@symPun	87
\@symRel	86
\@symVar	84, 96–98
\@symextension	332, 335
\@symtype	83–93, 96–98, 100, 265, 344
\@symtype@ord	344, 346
\@tempb	228, 233, 237, 334, 335
\@typeset@protect	16
\@undefined	364
\@vereq	718
_	35, 38, 41, 44, 349
\	400
A	
\active	225, 260
\aleph	568
\alpha	463
\amalg	597
\angle	708, 849
\approx	633
\approxeq	965
\Arrowvert	696
\arrowvert	695
\ast	565, 613
\asymp	651
\AtBeginDocument	363, 435, 566
\AtEndOfPackage	6
B	
\backepsilon	975

\backprime	818	\Cap	859, 860
\backsimeq	876	\cap	590
\backsimeq	877	\catcode	7, 12, 224, 225, 259, 260
\backslash	703	\cdot	612
\barwedge	847	\cdot_0	654, 655
\baselineskip	741	\cdot_p	655, 739
\Bbbk	972	\cdot_s	739
\because	803	\centerdot	765
\begingroup	227, 254, 261, 342, 348, 748	\char	257
\beta	464	\check@mathfonts	262
\beth	953	\chi	483
\between	832	\circ	609
\bigcap	660	\circceq	797
\bigcirc	610	\circlearrowleft	769
\bigcup	661	\circlearrowright	768
\bigodot	667	\circledast	881
\bigoplus	666	\circledcirc	880
\bigotimes	665	\circleddash	882
\bigsqcup	669	\circledS	873
\bigstar	831	\cleaders	292, 296, 300
\bigtriangledown	587	\clist	334
\bigtriangleup	586	\clubsuit	581
\biguplus	659	\colon	433
\bigvee	657	\complement	878
\bigwedge	658	\cong	718
\binrel@	326	\coprod	656
\binrel@@	305, 318–324	\copy	292, 297
\binrel@a	317, 329	\crcr	710, 711, 713
\binrel@sym	304, 329	\cs	34, 37, 40, 43, 50–62, 64, 67, 68, 71, 74, 78, 79, 83– 94, 96–98, 102–114, 116–143, 145–160, 162–189, 192, 194– 221, 228, 242, 244, 255, 263– 267, 270, 358, 408–418, 420, 422, 425, 427–429, 655, 758, 759
\blacklozenge	767	\csname	248
\blacksquare	764	\Cup	857, 858
\blacktriangle	837	\cup	591
\blacktriangledown	833	\curlyeqprec	812
\blacktriangleleft	835	\curlyeqsucc	813
\blacktriangleright	834	\curlyvee	862
\bot	576	\curlywedge	861
\bowtie	727	\curvearrowleft	968
\box	293, 298, 301	\curvearrowright	969
\boxdot	760		
\boxminus	772		
\boxplus	761		
\boxtimes	762		
\bracevert	694		
\buildrel	724		
\bullet	599		
\Bumpeq	868		
\bumpeq	867		
		D	
\c@ncel	722	\dagger	593
		\daleth	955
		\dashv	620
		\ddagger	592

C

\ddots	743	\epsilon	467
\DeclareFlexCompoundSymbol	247, 705, 707, 708,	\eqcirc	839
	716–718, 722–735, 739, 740, 743	\eqsim	952
\DeclareFlexDelimiter	242, 670–703	\eqslantgr	811
\DeclareFlexSymbol	226, 243, 430–	\eqslantless	810
	561, 563–654, 656–669, 704,	\equiv	650
	706, 760–782, 784–804, 806–	\eta	469
	857, 859, 861–869, 871, 873–975	\eth	951
\DeclareOption	14, 384, 386–388	\everymath	268
\DeclareRobustCommand	248, 251, 252, 281, 340, 341	\ExecuteOptions	389
\def	15, 19–33, 226, 247,	\exists	579
	253, 261, 269, 285, 291, 295,	\exp	16, 65, 69, 75, 76, 229, 230, 232,
	299, 304, 317–324, 326, 332,		244, 248, 313, 314, 335, 347, 414
	344, 346, 347, 350, 562, 748, 750	\expandafter	274
\Delta	438	\ExplSyntaxOff	752, 976
\delta	466	\ExplSyntaxOn	407, 756
\diagdown	914		
\diagup	913	F	
\diamond	598	\fallingdotseq	820
\diamondsuit	582	\fi	16, 238, 276,
\digamma	970		313, 356, 370, 371, 379, 380, 382
\displaylimits	47, 49	\Finv	948
\div	601	\flat	497
\divideontimes	945	\forall	578
\do	5, 11	\frown	504
\Doteq	805		
\doteq	724	G	
\doteqdot	804, 805	\Game	949
\dotplus	875	\Gamma	437
\doublebarwedge	848	\gamma	465
\doublecap	860	\gdef	318–324, 365, 374
\doublecup	858	\ge	395
\Downarrow	701	\geq	395, 630
\downarrow	698	\geqq	822
\downdownarrows	781	\geqslant	823
\downharpoonleft	786	\gets	398
\downharpoonright	784	\gg	642
\dp	287	\ggg	871, 872
		\gggtr	872
		\gimel	954
		\global	101
		\gnapprox	910
		\gneq	896
\edef	5, 224, 259, 751	\gneqq	892
\ell	494	\gnsim	902
\else	16, 234, 273, 307–	\gtapprox	800
	313, 354, 366, 368, 373, 375, 377	\gtrdot	957
\emptyset	573	\gtreqless	841
\endcsname	248	\gtreqqless	843
\endgroup	239, 257, 277, 342, 349, 749	\gtrless	824
\endinput	402		

\gtrsim	799	\lceil	675
\gvertneqq	884	\ldotp	562
		\ldotp\ldotp	562
		\le	394
		\leaders	713
		\leavevmode	281
		\Leftarrow	627, 731, 735
		\leftarrow	296, 300, 398, 645, 726, 732, 734
		\leftarrowfill	295
		\leftarrowtail	788
		\leftharpoondown	506
		\leftharpoonup	505
		\leftleftarrows	778
		\Leftrightarrow	626
		\rightleftarrows	644
		\leftrightharpoons	771
		\leftrightsquigarrow	794
		\leftthreetimes	863
		\leq	394, 629
		\leqq	815
		\leqslant	816
		\lessapprox	809
		\lessdot	956
		\lesseqgtr	840
		\lesseqgtr	842
		\lessgtr	817
		\lesssim	808
		\let	11, 13, 47–49, 100, 101, 233, 237, 249, 328, 329, 344, 345, 783, 805, 858, 860, 870, 872
		\lfloor	677
		\lgroupt	692
		\lhookRel	563, 725
		\lineskip	741
		\ll	643
		\Lleftarrow	845
		\lll	869, 870
		\llless	870
		\lmoustache	690
		\lnapprox	909
		\lneq	895
		\lneqq	891
		\lnot	391
		\lnsim	901
		\Longleftarrow	731
		\longleftarrow	732
		\Longleftrightarrow	735, 737

\longleftarrowrightarrow	734	\mathpunct	87, 655
\longmapsto	733	\mathrel	86, 93, 711
\Longrightarrow	729	\mathsm@sh	749
\longrightarrow	730, 733	\Mathstrutbox@	287
\looparrowleft	795	\measuredangle	850
\looparrowright	796	\mg@acc	24
\lor	393	\mg@arr	23
\lowercase	237, 275, 349	\mg@Bbb	30
\lozenge	766	\mg@bflatin	29
\Lsh	791	\mg@bin	19, 412, 427, 428
\ltimes	958	\mg@cal	31
\lVert	682	\mg@cop	25, 429
\lvert	684	\mg@del	22, 413, 429
\lvertneqq	883	\mg@digit	33, 414, 418
		\mg@frak	32
		\mg@Greek	28, 418, 420, 425
M		\mg@greek	27, 417
\m@Bin	52, 53, 104, 105	\mg@Latin	416
\m@COi	56, 108	\mg@latin	26, 415–417, 420, 425
\m@COs	55, 107	\mg@nre	21
\m@DeA	60, 112	\mg@OML	415
\m@DeB	59, 111	\mg@OMS	412
\m@DeL	57, 109	\mg@OMX	413
\m@DeR	58, 110	\mg@ord	428
\m@Ord	50, 102	\mg@rel	20, 427
\m@Pun	54, 106	\mho	950
\m@Rad	61, 113	\mid	619
\m@th	291, 295, 299, 710	\mkern	269, 270, 292–
\m@Var	51, 103		294, 296–298, 300–302, 705,
\mapsto	717		711, 713, 720, 721, 744–746
\mapstochar	733	\models	728
\mapstoOrd	653, 717	\mp	607
\math	34, 37, 40, 43, 50–62, 64, 65, 67–69, 71, 74, 75, 78, 83–94, 96–98, 102–114, 116– 143, 145–160, 162–189, 192, 194–221, 223, 306–312, 318– 324, 340, 352, 353, 355, 358, 359	\mskip	270, 737
\mathbin	85	\mu	474
\mathchar	749–751	\multimap	801
\mathchardef	369	\muskip	269
\mathchars@reset	342, 344		
\mathchoice	328		
\mathclose	91, 97		
\mathcode	. 235, 365–367, 369, 372, 374, 381		
\mathinner	98		
\mathop	88, 89, 707		
\mathopen	90, 96		
\mathord	83, 84, 92		
\mathpalette	718, 722, 723, 749		
		N	
		\nabla	574
		\namelimits	49
		\natural	498
		\ncong	912
		\ne	396
		\nearrow	622
		\neg	391, 580
		\neq	396, 716
		\newcommand	333, 339
		\newmcodes@	365, 374
		\nexists	947
		\ngeq	886

\ngeqq	904	\omega	485
\ngeqslant	894	\ominus	605
\ngtr	888	\oplus	606
\ni	397, 641	\OrdSymbol	83– 93, 96–98, 266, 294, 296, 300, 302, 314, 318–324, 340, 341, 345
\nLeftarrow	941	\oslash	603
\leftarrow	939	\otimes	604
\leftrightarrow	943	\over	724
\leftleftarrows	944	\owns	397
\leq	885		
\leqq	903		
\leqslant	893		
\less	887		
\nmid	928	\p@	741, 742, 744–746
\noalign	712	\parallel	618
\noexpand	6, 271	\partial	496
\nointerlineskip	712	\PassOptionsToPackage	385
\nolimits	48	\perp	649
\not	340, 716	\Phi	445
\notin	722	\phi	482
\notRel	340, 652, 711	\Pi	442
\nparallel	927	\pi	477
\nprec	889	\pitchfork	874
\npreceq	897	\pm	608
\nrightarrow	942	\prec	632
\nrightarrow	940	\precapprox	967
\nshortmid	929	\preccurlyeq	814
\nshortparallel	930	\preceq	635
\nsim	911	\precnapprox	907
\subsetneq	925	\precneqq	905
\subsetneqq	917	\precnsim	899
\nsucc	890	\precsim	807
\nsucceq	898	\prg	255
\supseteq	926	\prime	282, 572
\supseteqq	918	\ProcessOptions	390
\triangleleft	937	\prod	663
\trianglelefteq	936	\proto	615
\triangleright	938	\protect	16
\trianglerighteq	935	\providecommand	280, 719
\nu	475	\ProvidesExplFile	338
\number	7	\ProvidesExplPackage	3
\nDash	934	\ProvidesFile	339
\nDash	932	\ProvidesSymbols	339, 404–406, 755
\nvDash	933	\Psi	446
\nvdash	931	\psi	484
\narrow	624		
			R
		\raise	282, 744, 746
O			
\odot	602	\rangle	670
\oint	668	\rbrace	672
\Omega	447	\rceil	674

\Re	569	\smallfrown	854
\relax	8, 11, 232, 235, 236, 249, 271, 274, 345, 369, 372, 378, 381, 390, 757	\smallint	585
\Relbar	729, 731, 750, 751	\smallsetminus	962
\relbar	291, 295, 299, 730, 732, 748	\smallsmile	853
\renewcommand	391–400, 720, 721, 736	\smash@	748
\RequirePackage	2, 401, 757	\smile	503
\resetMathstrut@	285	\space	367, 376
\restriction	783	\spadesuit	584
\rfloor	676	\sphericalangle	851
\rgroup	693	\sqcap	594
\rho	478	\sqcup	595
\rhookRel	564, 726	\sqsubset	825
\Rightarrow	628, 729, 735	\sqsubseteq	616
\rightarrow	294, 302, 399, 646, 717, 725, 730, 734	\sqsupset	826
\rightarrowfill@	291	\sqsupseteq	617
\rightarrowtail	787	\square	763
\rightharpoondown	508	\star	502
\rightharpoonup	507	\std@minus	369, 378
\rightleftarrows	790	\string	274, 347, 751
\rightleftharpoons	723, 770	\Subset	855
\rightrightarrows	779	\subset	637
\rightsquigarrow	793	\subsetneq	639
\rightthreetimes	864	\subsetneqq	865
\risingdotseq	819	\subsetneqeq	923
\rlh@	723	\subsetneqqeq	919
\rmoustache	691	\succ	631
\rightarrow	844	\succapprox	966
\Rsh	792	\succcurlyeq	821
\rtimes	959	\succceq	634
\rVert	683	\succnapprox	908
\rvert	685	\succneq	906
		\succnsim	900
		\succsim	798
		\sum	664
		\sumlimits	47, 55, 89
		\Supset	856
S		\supset	636
\scriptchar	252	\supseteq	638
\scriptfont	252, 282	\supseteqq	866
\scriptstyle	710	\supsetneq	924
\searrow	623	\supsetneqq	920
\setbox	286, 327	\surd	707
\setboxz@h	291, 295, 299	\surdOrd	706, 707
\setminus	611	\swallow	625
\sharp	499	\sym@global	101, 233, 235, 237, 249
\shortmid	960	\symAMSA	758
\shortparallel	961	\symAMSb	759
\Sigma	443	\symlargesymbols	411
\sigma	479	\symletters	409
\sim	647, 718	\symoperators	408
\simeq	648		

\symsymbols	410	\upuparrows	780
\symupright	422, 751	\use	16, 65, 69, 75, 76, 81, 244, 265, 266, 268
T			
\tau	480	\usesymbols	333, 386–388
\tex	35, 38, 41, 44	V	
\text@char	251, 252, 261, 282	\varepsilon	486
\text@char@sym	253, 264	\varkappa	971
\text@script@char	256, 263	\varnothing	946
\textchar	251, 286	\varphi	491
\textfont	251	\varpi	488
\textprime	280, 281	\varpropto	852
\textstyle	724	\varrho	489
\the	224, 256, 259	\varsigma	490
\therefore	802	\varsubsetneq	915
\Theta	439	\varsubsetneqq	921
\theta	470	\varsupsetneq	916
\thickapprox	964	\varsupsetneqq	922
\thickmuskip	737	\vartheta	487
\thicksim	963	\vartriangle	836
\times	614	\vartriangleleft	828
\tmp	224, 241, 259, 279	\vartriangleright	827
\to	399	\vbox	709, 741, 745
\top	575	\vdash	773
\triangle	577	\vDash	775
\triangledown	838	\vdash	621
\triangleleft	500, 727	\vdots	740
\trianglelefteq	830	\vee	393, 589
\triangleq	806	\veebar	846
\triangleright	501, 727	\Vert	400, 686
\trianglerighteq	829	\vert	286, 687, 728
\twoheadleftarrow	777	\vDash	774
\twoheadrightarrow	776	W	
U			
\Umathcharnumdef	378	\wedge	392, 588
\Umathcode	364	\wp	495
\Umathcodenum	375, 376, 378	\wr	600
\Uparrow	700	X	
\uparrow	697	\xdef	305
\Updownarrow	702	\Xi	441
\updownarrow	699	\xi	476
\upharpoonleft	785	Z	
\upharpoonright	782, 783	\z@	224, 225, 236, 259, 260, 269, 274, 286, 287, 291– 293, 295, 297–299, 301, 327, 741
\plus	596	\zeta	468
\Upsilon	444		
\upsilon	481		